



VRLA Rechargeable Battery

BPL7-12 (BPL7-12FR)



FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

APPLICATION

- UPS
- Laboratory Equipment
- Toy-Cars
- Power Packs
- Fishing Lights



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	7.0Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	2600g(5.73lbs.)
Terminals	T2 (Faston Tab 250) T1 is optional
Internal Resistance	≤25m Ω (Fully Charged)
Max. Discharge Current	105 A (5 sec.)
Max. Charge Current	2.1 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)


ISO 9001	
ISO14001	
UL	
CE	
<ul style="list-style-type: none"> ● IEC 61056-1 ● JIS C 8702-1 ● GB/T 19639.1 	

DIMENSION(mm/inch)


OUTER DIMENSIONS

TERMINAL TYPE


- **Length**
151±1.5 (5.94±0.06)
- **Width**
65±1.5 (2.56±0.06)
- **Container Height**
93±1.5 (3.66±0.06)
- **Total Height**
98±2.0 (3.86±0.08)



● Terminal T1



● Terminal T2



Constant power discharge characteristics at 25 °C/77 °F

Unit: W

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		228.0	171.4	138.8	83.50	48.40	20.40	14.10	7.86	4.11
1.75V		264.0	185.7	145.3	86.70	49.80	20.80	14.30	7.98	4.20
1.70V		280.0	192.4	149.7	88.60	50.70	21.00	14.40	8.02	4.22
1.65V		293.0	197.0	153.2	89.90	51.40	21.20	14.50	8.04	4.23
1.60V		302.0	200.9	156.2	90.80	51.90	21.30	14.50	8.04	4.23

Constant current discharge characteristics at 25 °C/77 °F

Unit: A

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V		20.54	15.09	12.07	7.076	4.067	1.700	1.175	0.655	0.343
1.75V		24.22	16.35	12.63	7.347	4.185	1.733	1.192	0.665	0.350
1.70V		25.69	16.94	13.02	7.508	4.261	1.750	1.200	0.668	0.352
1.65V		26.88	17.34	13.32	7.619	4.319	1.767	1.208	0.670	0.353
1.60V		27.71	17.68	13.58	7.695	4.361	1.775	1.208	0.670	0.353

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.