



Notes:

1. Electrical:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Connector Operating Temperature: -40° C to +85° C
2. Materials and Finish:
 - Metal Coupling Ring: Brass, Nickel Plated
 - Plug Housing: Metallized ABS, UL94 V-0, Nickel Plated
 - Interfacial Seal: Silicone, Color: White
 - Cable Gland: Brass, Nickel Plated
 - Cable Gland Seal: NBR, Color: Black
 - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
 - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-0
 - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50 u" Gold min. over Nickel
 - Cable: See Part Number Table
3. RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

Cable Length L	Part Number		
	Cat. 5e STP 4 Pair, AWG24 Solid Black Cable	Cat. 5e Outdoor UTP 4 Pair, AWG24 Solid Black Cable	Cat. 5e Outdoor STP 4 Pair, AWG24 Solid Black Cable
2 m	17-100994	17-101084	17-101114
4 m	17-101004	17-101094	17-101124
5 m	17-101014	17-101104	17-101134

Notes: - Special cable length are available please contact factory
 - UTP: Unshielded Twisted Pair
 - STP: Shielded Twisted Pair

THIS DRAWING MAY NOT BE COPIED, REPRODUCED, IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in Meter
	Name	Title	Approval Date	Dimensional: Angles:			Autodesk Inventor	Material: See Notes
				2008	Date	Name		Title:
				Draw.	Dec. 12	Vincent Ke	RJ45 Cat. 5e Ethernet Patch Cord	
				Appd.	Dec. 12	J. Chaudry	Industrial to Industrial	
				Norm			Full Metal Version (RoHS Compliant)	
				D-old			Drawing No.: 17K1A113	
	b	Jan/29/2009	Vincent Ke				Part No.: SEE P/N ABOVE	
	a	original				DIN A3		
	Rev.	Changes	Date			Name	Sheet 1/1	