

NOTE :  
MATERIAL: BLACK, OIL RESISTANT, SYNTHETIC RUBBER SHEET, 75/85 DUROMETER. FLAT SURFACES TO BE SMOOTH & FREE OF DEPRESSIONS AND FLAWS.


2				
1				
NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

**BILL OF MATERIAL**

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.	
O	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

																			E	LTR
																				39046C-REVISE & REDRAWN IN NEW STRUCTURE 3/30/98 KAM
																				<b>REVISION</b>

COPIES TO	MATL SPEC	FINISH
1 9 18	DRW KAM	DATE 12/10/97
2 10 19		SCALE 4:1
3 12 20	CHK	DATE
4 13 21		SUPER DRW
5 14 23	APPD	DATE
6 15 33		RAW STK WT
7 16 43	TOLERANCE UNLESS OTHERWISE SPECIFIED	
8 17 53	TWO PLACE DEC ±.01	FRACTION
	THREE PLACE DEC ±.005	ANGULAR
<b>TITLE</b>		
WASHER		
<b>REVISION</b> / <b>DRWG. NO.</b>		


**Littelfuse®**  
 DES PLAINES, ILLINOIS 60016

-901-074  
 UNCONTROLLED DOCUMENT

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED