



NOTES:
 1. I.D. TO BE .455 "GO"/.471 "NO GO" WHEN MEASURED IN DIRECTION SHOWN.
 2. TO INSURE LANCE IS CUT FREE, PART TO BE BENT 90° AT EACH LANCE.

VENDOR: ASQUARED
 P/N: PO-659460-1

MUST BE LANCED FREE (4 PLACES) (SEE NOTE 2)

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.				
○	DENOTES CRITICAL CHARACTERISTICS.			
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE			
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.			
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.			
COPIES TO	MATL SPEC AISI C-1050 ANNEALED .625 W. x .012 THK HEAT TREAT TO RC 46-50		FINISH BLACK OXIDE	
1 9 18	DRW	JMB	DATE	SCALE 2=1
2 10 19			3/2/98	
3 12 20	CHK		DATE	SUPER DRW
4 13 21				
5 14 23	APPD		DATE	RAW STK WT
6 15 33				
7 16 43	TOLERANCE UNLESS OTHERWISE SPECIFIED			
8 17 53	TWO PLACE DEC ±.01		FRACT ON	
	THREE PLACE DEC ±.005		ANGULAR	
TITLE PUSH-ON ROUND				
Littelfuse®		REVISION		DRWG. NO.
DES PLAINES, ILLINOIS 60016				-903-114

G	LTR
39107C - REVISED & REDRAWN ON NEW FORMAT 4/21/98 JMB	REVISION
	CHK
	APD

UNCONTROLLED DOCUMENT

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED