

Circuit Protection Terminals

USI 16
1 Pole



USI 16
2 Pole



USI 16
3 Pole



**USI 16
w/ Neon Indication**
1 Pole



Warning:

In the event of a faulty fuse, the connected circuit has a leakage current flow equal to the indicator current specified.

Single Level
1 1/2" x 13/32" fuse

Single Level
1 1/2" x 13/32" fuse

Single Level
1 1/2" x 13/32" fuse

Single Level
1 1/2" x 13/32" fuse

Terminal Block Selection Data							
Available Options	Version	Part No.	Part No.	Part No.	Part No.	Part No.	Part No.
	White PA	991073	997504	991075		67601493	
Dimensions							
Width / Length / Height mm (in.)	for TS 35	17.5/66/80 (0.7/2.6/3.15)	35/66/80 (1.38/2.6/3.15)	52.5/66/80 (2.07/2.6/3.15)		17.7/78.5/61.2 (.70/3.09/2.41)	
Insulation stripping length	mm (in.)	10 (.39)	10 (.39)	10 (.39)		10 (.39)	
Technical Data							
Rated voltage / rated current / wire size	UL	600 V / 30 A / #18...6 AWG	600 V / 30 A / #18...6 AWG	600 V / 30 A / #18...6 AWG		600 V/30 A/#18...6 AWG	
	CSA	600 V / 30 A / #18...6 AWG	600 V / 30 A / #18...6 AWG	600 V / 30 A / #18...6 AWG			
Torque	Nm (lb. in.)	1.2 (10.5)	1.2 (10.5)	1.2 (10.5)			
Clamping screw	M	4	4	4			
Selected Accessory Data†							
Other Accessories	Print	Type	Part No.	Type	Part No.	Type	Part No.
Lever bar: 2 pole		2 pole	9975260000				
3 pole		3 pole	9975270000				
4 pole		4 pole	9975280000				
Screwdriver							9024230000
Handle Pen*							4000950000
Body Pen*							4000960000
Marking Tags							
Adhesive Tag, White		ESG9/17K	1674760000	ESG9/17K	1674760000	ESG9/17K	1674760000
Marking Pen, Black		STI-S	0508401694	STI-S	0508401694	STI-S	0508401694
Note: Part numbers shown are for blank adhesive markers.							

†See Accessories section for additional information.
 *Use to abut USI 16 with indication into multiple pole configurations.
 1 handle pen + 2 body pens = abuts 2 USI 16
 2 handle pens + 4 body pens = abuts 3 USI 16