



Electrical Characteristics IEC 60127-4

Testing current	Blow Time	
	Minimum	Maximum
125%	1 Hr.	N/A
200%	N/A	2 Min
1000%	0.01 Sec	0.1 Sec

Approvals IEC60127-4

Safety Agency Approvals	Amp range / volt @ I.R. ability
UL Listed File No. E315341	100mA- 6.3A / 250V @150A AC and 350V @100A AC
S Certified File No. 50345	6.3A / 250V @150A AC and 350V @100A AC Other ratings - available soon



RoHS 6 Compliant Product

RoHS Reflow Compatible reference: 240°C, 30 sec max

Environmental Specifications

Solder Process Window

IR Reflow: 240°C, 30 sec max
(Not Recommended For Wave Solder / Direct Immersion)

Shock Resistance

MIL-STD-202G, Method 213B, Test Condition I
(100 G's peak for 6 milliseconds ; Sawtooth Waveform).

Vibration Resistance

MIL-STD-202G, Method 201A
(10-55 Hz, 0.06 inch, total excursion).

Salt Spray Resistance

MIL-STD-202G, Method 101E, Test condition B (48 hrs).

Insulation Resistance

IEC 60127-4, 0.1Mohms minimum @500VDC (After Opening)

Solderability

IEC 60127-4

Soldering Heat Resistance

MIL-STD-202G, Method 210F, Test Condition J (235°C, 30 sec)

Thermal Shock Resistance

MIL-STD-202G, Method 107G, Test Condition B
(-65°C to +125°C).

Operating Temperature

-55°C to +125°C

Catalog Number	Ampere Rating	Typical Cold Resistance (ohm)	Volt-drop @100% In (Volt) max.	Melting I ² T @10 In (A ² Sec)	Maximum Power Dissipation (W)
UMTS 250	250mA	0.803	0.314	0.262	0.12
UMTS 315	315mA	0.555	0.279	0.419	0.14
UMTS 400	400mA	0.384	0.248	0.671	0.16
UMTS 500	500mA	0.266	0.221	1.07	0.19
UMTS 630	630mA	0.184	0.197	1.72	0.21
UMTS 800	800mA	0.127	0.175	2.75	0.25
UMTS 1	1A	0.088	0.156	4.40	0.28
UMTS 1.25	1.25A	0.061	0.139	7.04	0.33
UMTS 1.6	1.6A	0.059	0.110	5.60	0.37
UMTS 2	2A	0.045	0.108	9.24	0.43
UMTS 2.5	2.5A	0.035	0.106	15.2	0.50
UMTS 3.15	3.15A	0.027	0.104	25.2	0.57
UMTS 4	4A	0.021	0.101	41.5	0.66
UMTS 5	5A	0.016	0.099	68.5	0.75
UMTS 6.3	6.3A	0.012	0.097	113	0.87

Consult manufacturer for other ratings

HALOGEN FREE= HF

LEAD FREE = (Pb)

Physical Specifications

Materials

Ceramic body / Brass Caps , gold plated with nickel undercoating

Marking

On fuse:
"bel", "T", "Current Rating", "L", "250V", "M".


Label on reel :

"bel", "UMTS", "Current Rating", "Voltage Rating", "Interrupting Rating",
"Appropriate Safety Logos" and "M", "E" (China RoHS compliant)

Packaging


1,500 fuses in 13 inches dia. Reel, 24 mm wide tape, per EIA Standard 481-C

Mechanical Dimensions



ORDERING INFORMATION SEE LAST 2 PAGES

UMTS - TIME CURRENT CHARACTERISTIC CURVE



Specifications subject to change without notice

NOTE - see important information under "User Guide" on P.08

Corporate Office
Bel Fuse Inc.
 206 Van Vorst Street, Jersey City, NJ 07302
 Tel: 201-432-0463
 Fax: 201-432-9542
 E-Mail: belfuse@belfuse.com
 Website: www.belfuse.com

Far East Office
Bel Fuse Ltd.
 8F/8 Luk Hop Street
 San Po Kong
 Kowloon, Hong Kong
 Tel: 852-2328-5515
 Fax: 852-2352-3706

European Office
Bel Fuse Europe Ltd.
 Preston Technology Management Centre
 Marsh Lane, Preston PR1 8UQ
 Lancashire, U.K
 Tel: 44-1772-556601
 Fax: 44-1772-888366