

## LOW VOLTAGE

### SFE Fast-Acting Type



#### ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, <b>Minimum</b>
135%	1 hour, <b>Maximum</b>
200%	10 seconds, <b>Maximum</b>

**APPROVALS:** Listed by Underwriters Laboratories.


**DESIGN STANDARDS:** U.L. Standard 275. SAE (Society of Automotive Engineers) J554.

#### ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Fuse Length
307 004	4	32	5/8"
307 006	6	32	3/4"
307 07.5	7½	32	7/8"
307 009	9	32	7/8"
307 014	14	32	1¼"
307 020	20	32	1¼"
307 030	30	32	1¾"



### 3AG Fast-Acting Type



#### ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
100%	4-35	4 hours, <b>Minimum</b>
135%	4-35	1 hour, <b>Maximum</b>
200%	4-30	10 seconds, <b>Maximum</b>
200%	35	20 seconds, <b>Maximum</b>

**APPROVALS:** Listed by Underwriters Laboratories and Certified by CSA through 30 amperes.

**DESIGN STANDARDS:** U.L. Standard 275.

#### ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
311 004	4	32
311 005	5	32
311 006	6	32
311 007	7	32
311 07.5	7½	32
311 008	8	32
311 010	10	32
311 012	12	32
311 015	15	32
311 025	25	32
311 030	30	32
311 035	35	32

For 20-ampere rating use 307 020.

