


- △ HOUSING MATERIAL: GLASS-FILLED POLYESTER. COLOR: GRAY.
- △ CONTACT MATERIAL: PHOSPHOR BRONZE.
- △ CONTACT FINISH: 0.00076[0.00030] GOLD IN CONTACT AREA. 0.00127[.00050] NICKEL UNDERPLATE ALL OVER. TIN-LEAD ON POSTS.
- △ PART NUMBER, DATE CODE IDENTIFICATION, CSA LOGO IN THIS APPROXIMATE AREA, ON REVERSE SIDE.
- △ POINT OF MEASUREMENT FOR GOLD.
- △ RECOMMENDED HOLE SIZE FOR MANUAL APPLICATION OF CONNECTOR ONTO PC BOARD.
- △ CONTACT FINISH: 0.00127[.00050] GOLD IN CONTACT AREA. 0.00127[.00050] NICKEL UNDERPLATE ALL OVER. TIN-LEAD ON POSTS.
- △ CONTACT FINISH: DIN 41612 CLASS 3 IN CONTACT AREA. TIN-LEAD ON POSTS.
- △ CONTACT FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN-LEAD ON POSTS.
- △ CONTACT FINISH: GOLD FLASH OVER 1.02μm[.000040] MIN PALLADIUM/NICKEL IN CONTACT MATING AREA. ALL OVER 1.27μm[.000050] MIN NICKEL. TIN-LEAD ON TAILS.



SECTION X-X

| | | | | | | |
|----------|------------------|---|---|---|--------|------------------|
| OBSOLETE | 1 THRU 32 | X | X | X | 96 | 535043-9 |
| OBSOLETE | 1 THRU 32 | X | X | X | 96 | 535043-6 |
| OBSOLETE | 1 THRU 32 | X | X | X | 96 | 535043-5 |
| OBSOLETE | 1 THRU 32 | X | X | X | 96 | 535043-4 |
| OBSOLETE | 1 THRU 32 | X | X | X | 96 | 535043-1 |
| NOTE | POSITIONS LOADED | C | B | A | 100-96 | ASSY PART NUMBER |

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 12/24/01

DESIGNED BY: R. PATTERSON DATE: 12/24/01

ASSEMBLY, RECEPTACLE, EUROCARD, TYPE C, SOLDER TAIL, 96 POSITION

DATE: 12/24/01 DRAWING NO: A100779(535043)

CUSTOMER DRAWING