



LOC	DIST	REVISIONS			
F	UR	DESCRIPTION	DATE	UR	APP
H	-	L	EH10-0680-05	30-05-06	BSV BM
		L1	ECR-06-002635	07-02-06	BSV BM
		L2	REVISED PER ECO-09-021826	09JAN10	KK AEG

P.C.B. HOLE DIM. ACTION PIN  
FOR DETAILS SEE  
APPLICATION SPECIFICATION

- NOTES:**
- 1 MATERIAL HOUSING : GREY GLASSFILLED POLYESTER
  - CONTACT : UL-RATING V0
  - CONTACT : PHOSPHORBRONZE
  - GENERAL PLATING SPECIFICATION: UNDERPLATING (ENTIRE CONTACT): 1,27µm NICKEL MIN. AND ACTION PIN: 0,5µm TIN-LEAD MIN. FOR PLATING OF MATING SURFACES SEE APPLICABLE SPECIFICATION REFERENCE FOR EACH DASH NUMBER.
  - CONFORMS TO ALL TESTING ACCORDING IEC 61076-4-101 PERFORMANCE LEVEL 2.
  - CONFORMS TO ALL TESTING ACCORDING IEC 61076-4-101 PERFORMANCE LEVEL 1.
  - CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III, CENTRAL OFFICE APPLICATIONS.
  - CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III, UNCONTROLLED ENVIRONMENT APPLICATIONS.
  - CONNECTOR LUBRICATED WITH TELCORDIA GR-1217-CORE APPROVED LUBRICANT.
  - CONNECTOR ASSEMBLY WITH LATCH HINGE FOR CABLE CONNECTOR.
  - CONNECTOR MARKED WITH PARTNUMBER AND DATECODE
  - PLATED-THROUGH HOLES AT 2x2mm SQUARE GRID.
  - HOLES IN ROW f FOR POSSIBLE FUTURE USE OF GROUND RETURN SHIELDS. (NOT YET TOOLED)
  - OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINIS!

OBsolete	Y	△	△△	1-106012-9	
	N	△	△△△	1-106012-1 △	
OBsolete	Y	△	△△	106012-9	
	N	△	△△	106012-4	
	N	△	△△	106012-1	
			CONSERVATION TREATMENT	MATERIAL	PARTNUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DRN	L.v.d.HEIJDEN	1506297	 Tyco Electronics Corporation s-Hertogenbosch, Netherlands.
		DRK	D. TRUIJEN	1506297	
DIMENSIONS: MM		TOLERANCES UNLESS OTHERWISE SPECIFIED:	APPV	E.V. KONINGSBRUGGE	NAME
		0 P.L.C. # -			PRODUCT SPEC
		1 P.L.C. # -			APPLICATION SPEC
		2 P.L.C. # -			114-19029
		3 P.L.C. # -			SIZE
		4 P.L.C. # -			A2
		ANGLES # -			CAGE CODE
		FINISH # -			00779
					DRAWING NO
					106012
					RESTRICTED TO
					-
					CUSTOMER DRAWING
					SCALE
					NTS
					SHEET
					1 of 1
					REV
					L2

106012

A