

PC BOARD REAR TRANSITION MODULE
(CONNECTOR SIDE)
SCALE 5:1

LOC	DIST
GP	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	1	PROPOSED	24FEB2006	RT	GG
	A	REV PER ECO-06-021305	19SEP2006	BC	GG
	B	PER ECO-08-023222	17SEP2008	RT	GG
	C	REV PER ECO-08-026690	10NOV2008	BC	GG

1. HOUSING: LCP, UL94V0, COLOR: BLACK.
   CONTACT: PHOSPHOR BRONZE.
2. FINISH: 1.27µm GOLD IN CONTACT AREA 1.27µm MIN. TIN-LEAD ON PCB TAIL OVER 3.81µm MI NICKEL OVER ALL.
3. MANUFACTURING TOLERANCE FOR:
   Ø0.56±0.05 FINISHED HOLE WITH Sn PB PLATING:
   DRILLED HOLE = Ø0.65±0.02
   COPPER PLATING = 0.025-0.050
   Sn PB PLATING = 0.0038-0.0124
   OR
   Ø0.575±0.05 FINISHED HOLE WITHOUT Sn PB PLATING:
   DRILLED HOLE = Ø0.65±0.02
   COPPER PLATING = 0.025-0.050
4. ADDITIONAL CONNECTOR-SIDE KEEPOUT AREA REQUIRED IF CONNECTOR-SIDE EXTRACTION TOOL IS TO BE USED.
5. FINISH: 1.27µm GOLD IN CONTACT AREA 1.27µm MIN. TIN ON PCB TAIL OVER 3.81µm MI NICKEL OVER ALL.

2	1410965-2
1	1410965-1
PLATING	PART NO

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

DWN	24FEB2006	Tyco Electronics
CHK	24FEB2006	Harrisburg, PA 17105-3608
APVD	10NOV2008	
PRODUCT SPEC	108-2072	CONNECTOR ASSEMBLY,BACKPLANE VERTICAL RECEPTACLE, CENTER, 2.3mm, MULTIGIG RT 2
APPLICATION SPEC	114-13056	
SIZE	CAGE CODE	DRAWING NO
A1	00779	C-1410965

D.TREA
G.GRIFFITH
G.GRIFFITH
DIMENSIONS: MM
TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±1
1 PLC ±0.5
2 PLC ±0.13
3 PLC ±
4 PLC ±
ANGLES ±2°
MATERIAL
FINISH
WEIGHT -
CUSTOMER DRAWING
SCALE 2:1 SHEET 1 OF 1 REV C
RESTRICTED TO -

AMP 4805 REV 31MAR2000
Pro/ENGINEER DRAWING

Downloaded from Elcodis.com electronic components distributor