



REV. NO.		REVISIONS	
DATE	BY	DESCRIPTION	APP'D
01	BM	REVISED PER ECO-09-024927	KK AEG
0	BM	RELEASED PER ECO-0512-0327-04	RW

- △ HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER ASTM D5138 LCP000 G30A 32250, COLOR: NATURAL.
- △ CONTACT MATERIAL: PHOSPHOR BRONZE.
- △ CONTACT FINISH:
UNDERPLATE (ENTIRE CONTACT):
0.00127 MIN NICKEL PER SAE-AMS-QQ-N-290.
ON MATING SURFACES:
CONFORMS TO ALL TESTING SPECIFIED FOR TELCORDIA UNCONTROLLED ENVIRONMENT.
ON LEADS:
0.0008 MIN TIN PER ASTM B 545 OVER UNDERPLATE.
LUBRICATION (MIN MATING SURFACES):
SURFACE CONDITIONER AFTER PLATING.
- △ PART MARKING, LOCATED APPROXIMATELY AS SHOWN.
- △ DIMENSION APPLIES WHEN SEATED ON PRINTED CIRCUIT BOARD.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



REV. NO.	DATE	BY	DESCRIPTION	APP'D	
10	5	11.88	△	24	5536524-9
58	29	59.88	△	120	5536524-6
94	47	95.88	△	192	5536524-4
46	23	47.88	△	96	5536524-3
22	11	23.88	△	48	5536524-2
118	59	119.88	△	240	5536524-1

REV. NO.	DATE	BY	DESCRIPTION	APP'D	
10	5	11.88	△	24	5536524-9
58	29	59.88	△	120	5536524-6
94	47	95.88	△	192	5536524-4
46	23	47.88	△	96	5536524-3
22	11	23.88	△	48	5536524-2
118	59	119.88	△	240	5536524-1

REV. NO.	DATE	BY	DESCRIPTION	APP'D	
10	5	11.88	△	24	5536524-9
58	29	59.88	△	120	5536524-6
94	47	95.88	△	192	5536524-4
46	23	47.88	△	96	5536524-3
22	11	23.88	△	48	5536524-2
118	59	119.88	△	240	5536524-1

RECOMMENDED CIRCUIT PATTERN
PER IPC-D300 TYPE II, CLASS C
(COMPONENT SIDE)