







ASSEMBLY #	CONTACT PLATING
74029-6000	SEE NOTE 2.
74029-6050	SEE NOTE 3.



- NOTES:
1. MATERIALS: HOUSING - GLASS FILLED LIQUID CRYSTAL POLYMER, UL 94V-0, BLACK; TERMINAL - COPPER ALLOY.
  2. FINISH: SELECT GOLD IN CONTACT AREA, 30 microINCH THICK; TIN/LEAD IN COMPLIANT AREA.
  3. FINISH: SELECT GOLD IN CONTACT AREA, 50 microINCH THICK; TIN/LEAD IN COMPLIANT AREA.
  4. USE 6.0 mm NOMINAL FOR BACKPLANE LAYOUT.
  5. DIMENSION IS MEASURED FROM BOTTOM OF HOUSING.
  6. PACKED PER PK-70873-0876.
  7. THIS DIMENSION TO BE MULTIPLE OF 2.00 mm AS REQUIRED.

INITIAL RELEASE EC NO. UDT2001-0540 DRW: ELO 01/05/02 CHK: GORSKI 01/05/03 APPR: BIXLER 01/05/07	QUALITY SYMBOLS MAJOR = 0 CRITICAL = 0	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE 4 : 1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	DIMENSIONS:	SHT REV
		4 PLACES ±0.1 ±.	3 PLACES ±0.1 ±.	2 PLACES ±0.1 ±.	1 PLACE ±0.1 ±.	DRAWN BY & DATE ELO 01/50/02	CHECKED BY & DATE GORSKI 01/05/03	APPROVED BY & DATE BIXLER 01/05/07
REV A	DESCRIPTION	ANGULAR ± °		CAD FILENAME SD-74029-006.S01	MATERIAL NO. SEE CHART	DRAWING NO. SD-74029-006	SHEET NO. 1 OF 1	SIZE B

NOTES:

1. MATERIALS:

HOUSING - LIQUID CRYSTAL POLYMER (LCP),  
UL94 V-0, COLOR: BLACK.

TERMINAL - COPPER ALLOY

2. FINISH: 30 μ IN MIN. GOLD ON MATING SURFACE,  
TIN/LEAD ON TAILS; NICKEL UNDERPLATE.






3. FINISH: 50 μ IN MIN. GOLD ON MATING SURFACE,  
TIN/LEAD ON TAILS; NICKEL UNDERPLATE.

4. THIS PART CONFORMS TO PRODUCT SPECIFICATION  
PS-74031-999.

5. SINGLE ROW ASSEMBLY PACKED PER PK-70873-0876.

6. MATES WITH 74026 SERIES DAUGHTERCARD POWER ASSEMBLY.

7. MATING INTERFACE MEASURED FROM BOTTOM OF HOUSING.







SINGLE ROW ASSEMBLY

MOLEX P/N	GOLD THICKNESS
74029-6000	30uin
74029-6050	50uin

ADD TOLERANCE EC NO: UCP2009-3005 DRAWN BY: SMART 2009/06/15 CHKD: SDANNELLE09/06/16 APPR: SMILLER 2009/06/16 DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
	▽ -0 ▽ -0	mm INCH	4 PLACES ± --- ± ---	DIMENSION STYLE MM ONLY		TITLE
		3 PLACES ± --- ± ---	2 PLACES ± 0.25 ± ---	DRAWN BY ELO	DATE 2003/07/14	VHDM/HSD POWER 6 ROW BACKPLANE SALES ASSEMBLY
		1 PLACE ± --- ± ---	ANGULAR ± 5 °	CHECKED BY STANFORD	DATE 2003/07/17	MOLEX INCORPORATED
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY BIXLER	DATE 2003/07/21	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-74029-011	SHEET NO. 1 OF 3
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

- NOTES:
1. THIS DESIGN INTENDED AS OPTION TO HAVING TWO SINGLE ROW MODULES NEXT TO EACH OTHER.
  2. FINISH: 30 μ IN GOLD ON MATING SURFACE, TIN/LEAD ON TAILS; NICKEL UNDERPLATE.
  3. FINISH: 50 μ IN GOLD ON MATING SURFACE, TIN/LEAD ON TAILS; NICKEL UNDERPLATE.
  4. DUAL ROW ASSEMBLIES PACKED PER PK-70873-545.




DUAL ROW ASSEMBLY


MOLEX P/N	CONTACT PLATING
74029-6002	SEE NOTE 2.
74029-6052	SEE NOTE 3.

SEE SHEET 1 EC NO: UCP2009-3005 DRWN:BSMART 2009/06/15 CHKD:SDANNELL2009/06/16 APPR:SHILLER 2009/06/16	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	
	▼ -0 ∇ -0	mm      INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.25 ± --- 1 PLACE ± --- ± ---	DIMENSION STYLE MM ONLY	DRAWN BY ELO	DATE 2003/07/14	TITLE	VHDM/HSD POWER 6 ROW BACKPLANE SALES ASSEMBLY
		ANGULAR ± 5 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CHECKED BY STANFORD	DATE 2003/07/17	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-74029-011
	REV D			APPROVED BY BIXLER	DATE 2003/07/21	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-74029-011


# BOARD LAYOUTS: 1.8 mm MIN. BOARD THICKNESS




VHDM DUAL ROW POWER



VHDM-HSD SINGLE ROW POWER



VHDM-HSD DUAL ROW POWER



VHDM SINGLE ROW POWER

**NOTES:**

1. ADDITIONAL SPACING CAN BE ADDED IN MULTIPLES OF 2.0 mm AS REQUIRED. FOR EACH ADDITIONAL SINGLE ROW POWER, ADD 6.00 mm.
2. SIGNAL ROW A IS IN LINE WITH DATUM Y IN ALL FOUR LAYOUTS.
3. FOUR HOLES ARE USED PER POWER CONTACT.
4. EACH POWER HOLE TO BE MANUFACTURED AS FOLLOWS:  
 $\phi 0.725 \pm 0.075$  PLATED THROUGH HOLE  
 $\phi 1.20$  PAD  
 $\phi 0.838$  DRILL  
 $\phi 0.10 \times Y$

SEE SHEET 1 EC NO: UCP2009-3005 DRWN: BSMART 2009/06/15 CHKD: SDANNELL 09/06/16 APPR: SMILLER 2009/06/16	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
	0 0	mm INCH	DIMENSION STYLE MM ONLY	TITLE		
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.25 ± --- 1 PLACE ± --- ± --- ANGULAR ± 5 °	DRAWN BY DATE	VHDM/HSD POWER 6 ROW BACKPLANE SALES ASSEMBLY		
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CHECKED BY DATE	MOLEX INCORPORATED			
	APPROVED BY DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
	BIXLER 2003/07/21	SEE SHT 1 & 2	SD-74029-011	3 OF 3		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						