



### FEATURES:

- Converts BNC cables with male plugs to stackable banana plugs for versatility
- BNC connector and banana plugs are molded directly to the wire for pull strength durability and dust and moisture resistance
- BNC center contact is gold plated Beryllium Copper for corrosion resistance, low contact resistance and long insertion life

### MATERIALS:

BNC: Nickel plated brass  
 Center Contact: Gold plated Beryllium Copper  
 Wire: 18 AWG, PVC  
 Marking: "Pomona 3073"  
 Banana Plugs: Nickel plated brass  
 Spring: Nickel plated Beryllium Copper  
 Insulation: Polypropylene, red and black

### RATINGS:

Operating Voltage: Hand-held testing: 30VAC/60VDC Max.  
 Hands free testing in controlled voltage environments: 500 WVDC Max.

Operating Temperature: +55°C (+131°F) Max.

### ORDERING INFORMATION: Model 3073

Custom lengths are available, contact Pomona Technical support: 800-241-2060  
 (Technicalsupport@pomonatest.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060  
 For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)