



### FEATURES:

- Low profile 1.6 (.062) thick brass shorting bar.
- Center hole accepts #4-40 screw, for easy removal.
- Mates to Model # 2143 or any miniature double banana jack.

### MATERIALS:

#### Shorting Bar:

Material: Brass per QQ-B-613, composition 2, ½ Hard.

Finish: Gold plated per MIL-G-45204, Type II, Class 00 over electroless nickel per MIL-C-26074, 200/300 microinches.

#### Miniature Double Banana Plug:

##### Spring:

Material: Beryllium Copper per QQ-C-533, Alloy C172, Cond. HT.

Finish: Gold plated per MIL-G-45204, Type II, Class 00 over electroless nickel per MIL-C-26074, 200/300 microinches.

### RATINGS:

Current: 5 Amperes

Resistance: Resistance less than 1.5 milliohms.

### ORDERING INFORMATION: Model 3030

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

S:\Engineering\Release\DataSheets\FI\ukeDataSheet\3030\_1\_01.doc

Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90570 (800) 444-6785 or (425) 446-6010

More drawings available at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

Page 1 of 1