



FEATURES:

- Easy to assemble threaded two piece construction enables solderless wire attachment by means of an internal set screw
- Compatible with 18 to 22 AWG wire
- Banana plug spring is Beryllium Copper for long insertion life
- Banana plug body and spring are nickel plated for tarnish resistance

MATERIALS:

Plug Body: Brass, Nickel Plated

Plug Spring: Beryllium Copper, Nickel Plated

Insulation: Nylon

Set Screw: Brass

RATINGS:

Operating Voltage: 750V AC/DC (Independent of Wire)

Current: 25 Amperes Max.

ORDERING INFORMATION: Model 5934-* * = Color Code; Standard Colors: -0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue and -9 White Sold in packages of 10 per color.

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

C:\Laura Goldberg\FlukeDataSheet\5934_1_01.doc

Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90304 (800) 444-6785 or (425) 446-6010

More drawings available at www.pomonaelectronics.com

Page 1 of 1