


HOLE LAYOUT
(TOP VIEW)



SPECIFICATIONS:
 RATING: 12V DC @ 1A
 CONTACT RESISTANCE:
 30 MOHMS MAX
 INSULATION RESISTANCE:
 100 MOHMS MIN @ 500V DC
 WITHSTAND VOLTAGE:
 500V AC FOR 1 MINUTE
 LIFE: 5,000 CYCLES

NO.	DESCRIPTION	MATERIAL	QTY	FINISH
7	HOUSING	PBT	1	BLACK COLOR
6	BARREL	BRASS	1	NICKEL PLATED
5	TIP SPRING	0.25T TiCuR1-M-EH	1	SILVER PLATED
4	BREAK TERMINAL	0.3T BRASS	1	SILVER PLATED
3	BREAK TERMINAL	0.3T BRASS	1	SILVER PLATED
2	RING SPRING	0.2T TiCuR1-M-EH	1	SILVER PLATED
1	EARTH TERMINAL	0.2T PHOSPHOR BRONZE	1	SILVER PLATED

CUI INC
 9015 SW Allen, Suite 103
 Beaverton, OR 97006
 Phone: (503) 643-4899
 800-276-4899
 Fax: (503) 372-1266
 Website: www.cui.com

TITLE: **3.5mm AUDIO JACK-STEREO**

PART NO. **SJ-3525NG** UNITS: **MILLIMETERS**

DRAWN BY: **Todd R. White** APPROVED BY: SCALE: **3X**