



SPECIFICATIONS:

RATING: 12V DC @ 1A
 CONTACT RESISTANCE:
 30 MOHMS MAX
 INSULATION RESISTANCE:
 100 MOHMS MIN @ 500V DC
 WITHSTAND VOLTAGE:
 500V AC FOR 1 MINUTE
 LIFE: 5,000 CYCLES

ND.	DESCRIPTION	MATERIAL	QTY	FINISH
7	COVER	PBT	1	BLACK COLOR
6	HOUSING	PBT	1	BLACK COLOR
5	TIP SPRING	0.25T PHOSPHOR BRONZE	1	SILVER PLATED
4	BREAK TERMINAL	0.4T BRASS	1	SILVER PLATED
3	BREAK TERMINAL	0.4T BRASS	1	SILVER PLATED
2	RING SPRING	0.3T PHOSPHOR BRONZE	1	SILVER PLATED
1	EARTH TERMINAL	0.5T BRASS	1	SILVER PLATED



9815 SW Allen, Suite 103
 Beaverton, OR 97006
 Phone: (503) 643-4899
 800-276-4899
 Fax: (503) 372-1266
 Website: www.cui.com

TITLE: **3.5mm AUDIO JACK-STEREO**

PART NO.: SU-3555NG UNITS: MILLIMETERS
 DRAWN BY: Todd R. White APPROVED BY: SCALE: 3X