



HOLE LAYOUT  
(TOP VIEW)



**SPECIFICATIONS:**

RATING: 12V DC @ 1A  
 CONTACT RESISTANCE:  
 30 MOHMS MAX  
 INSULATION RESISTANCE:  
 100 MOHMS MIN @ 500V DC  
 WITHSTAND VOLTAGE:  
 500V AC FOR 1 MINUTE  
 LIFE: 5,000 CYCLES

ND.	DESCRIPTION	MATERIAL	QTY	FINISH
5	COVER	PBT	1	BLACK COLOR
4	HOUSING	PBT	1	BLACK COLOR
3	TIP SPRING	0.25T PHOSPHOR BRONZE	1	SILVER PLATED
2	RING SPRING	0.3T PHOSPHOR BRONZE	1	SILVER PLATED
1	EARTH TERMINAL	0.5T BRASS	1	SILVER PLATED



9815 SW Allen, Suite 103  
 Beaverton, OR 97006  
 Phone: (503) 643-4899  
 800-276-4899  
 Fax: (503) 372-1266  
 Website: www.cui.com

TITLE: **3.5mm AUDIO JACK-STEREO**

PART NO.: SU-3553NG UNITS: MILLIMETERS  
 DRAWN BY: Todd R. White APPROVED BY: SCALE: 3X