



- △ HOUSING: LIQUID CRYSTAL POLYMER, COLOR BLACK.
CONTACTS: HIGH RELIABILITY COPPER ALLOY.
GROUND BUSES: PHOSPHOR BRONZE ALLOY, UNS C51100.
- △ CONTACTS & GROUND BUSES: NICKEL UNDERPLATE ALL OVER,
MATING SURFACE PLATED TO MEET LEVEL 2 PERFORMANCE
REQUIREMENTS OF THE PRODUCT SPECIFICATION 108-1422,
SOLDER TAILS PLATED MATTE TIN.
- △ DATE CODE MARKED IN AREA INDICATED ON SAME SIDE AS
POSITION #1.
- △ ONE GROUND BUS WITH 5 TAILS PER EACH MODULE.
- △ TOLERANCE NON-ACCUMULATIVE.
- △ OBSOLETE

3.000[76.2]	6	3.450[87.63]	3.898[99]	4.000[101.6]	266	5767055-7
2.500[63.5]	5	2.950[74.93]	3.398[86.31]	3.500[88.9]	228	5767055-6
2.000[50.8]	4	2.450[62.23]	2.898[73.61]	3.000[76.2]	190	5767055-5
1.500[38.1]	3	1.950[49.53]	2.398[60.91]	2.500[63.5]	152	5767055-4
1.000[25.4]	2	1.450[36.83]	1.898[48.21]	2.000[50.8]	114	5767055-3
.500[12.7]	1	.950[24.13]	1.398[35.51]	1.500[38.1]	76	5767055-2
.000[0]	0	.450[11.43]	.898[22.81]	1.000[25.4]	38	5767055-1

E	D	C	B	A	NO. OF POS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 08/01/81 BY: J. ATTALA FOR: Type Electronics Corporation, Harrisburg, PA 17105-2608.

DESIGNER	DATE	PLUG ASSEMBLY, RIGHT ANGLE, .02[0.64] CENTER LINE, .062[1.57] PCB, MICTOR
DRW	108-1422	
CHK	114-13088	
APP	AMP-1422	
REV	A1	00779
SCALE	B:1	5767055

RECOMMENDED PC BOARD LAYOUT
 (MIRROR IMAGE ON OPPOSITE SIDE)