Ultraslim Trackball Keyboard G84-4420

This high-quality compact keyboard with integrated optical Trackball is designed for all applications where reliability, reduced space requirements and low height are of great importance. Useful for IT, industrial usage and medical facilities. Equally suitable for 19 inch rack-mounted drawers.



Facts & Features

- Single mechanical keys with Gold Crosspoint contacts (Cherry ML Modules)
- Designed for continuous use more than 20 Mio. key presses
- Robust and reliable with precise key actuation
- Integrated high quality Optical Trackball plus 2 mouse buttons
- Ultra slim only 20 mm overall height
- Lightweight
- Usable with standard drivers of the operating system
- Ideal for industrial usage with space limitations and for 19" applications
- Also available without housing for OEM

Agency Approvals

- CE, VDE/ÜG (EN60950), FCC, cUR, VCCI, BSMI, C-Tick, GOST-R
- Designed for MS Windows[®] XP
- MS Windows[®] Vista, Linux compatible

Delivery Volume

Keyboard, Manual

System Requirements

- PS/2: Plugs for Keyboard and Mouse
- USB: USB plug & supporting operating system

Technical Data

- Interface USB or 2x PS/2
- <u>Technology (USB Variant)</u>
 USB 2.0 (1.1 compatible), HID conform
 Bus powered, composite device, low speed
- Cable Length approx. 1.75 m
- Number of Keys
 83 = intern. layout without Windows[™] keys
 84 = europ. layout without Windows[™] keys
 Integrated Numeric Keypad
- Trackball
 Scanning: contactless, optical
 Resolution: 400 dpi
- Weight approx. 563 g (keyboard) approx. 720 g (without packaging)
- Dimensions
 approx. 370 x 139 x 19,6 mm (keyboard)
 approx. 400 x 195 x 32 mm (packaging)
- Current Input (3 LEDs on)
 USB: typ. 36 mA
 PS/2: typ. 24 mA (keyboard)
 - typ. 11 mA (trackball)
- Reliability
 MCBF > 10⁹ operations
 MTBF > 100.000 hours
- Storage Temperature
 -20 °C to 60 °C
- Operating Temperature 0 °C to 40 °C
- Operating life time of individual keys
 > 20 Mio operations
- Packaging Unit

 140 keyboards per master carton
 2 master cartons per pallet
- Warranty2 years



Order Description

Order Number	Trackball Scanning	Interface	Colour
G84-4420LUBxx-0	optical	USB	light grey
G84-4420LUBxx-2	optical	USB	black
G84-4420LPBxx-0	optical	2 x PS/2	light grey
G84-4420LPBxx-2	optical	2 x PS/2	black

The xx in the order number defines the country version:

Possible european layouts:

ΒE Belgium CH Switzerland DE Germany DK Denmark ES Spain FR France GB **UK-English** HU Hungary ΙT Italy NO Norway

PL Poland PO Portugal

SF Sweden / Finland

SK Slovakia

TS Czech Republic

TQ Turkey

Possible international layouts:

EU US English with €

JK Japan

KR US-English / Korea
RB US-English / Cyrillic
RC US-English / China

RC US-English / China

Cherry GmbH Cherrystraße

91275 Auerbach/Opf.

Germany

(Other country versions upon request)

Phone: +49 9643 18 0 Internet: <u>www.cherry.de</u>

Sales: +49 1805 243779 (+49 1805 CHERRY)

E-Mail: <u>sales@cherry.de</u> Fax: +49 9643 18 1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 Cherry GmbH, Last update: Jan 07, 2008_V02

