

Wipe-key Keyboard

J84-4300

This Slim, low profile, compact keyboard with integrated pointing device offers an IP55 rating for protection against dust and spraying liquids. It's ideal for applications requiring frequent disinfection for elimination of germs. Uses include diagnostics equipment, medical carts, rack mount servers, laboratories, and kiosks.



Facts & Features

- Membrane technology provides dust, dirt, and spraying water protection.
- Designed for continuous use – more than 10 Million key operations
- High reliability and uniquely precise tactile keying
- Full 87 US key layout
- Ultra slim - overall height only 19 mm
- Uses Standard Operating System Drivers
- Ideal for use with space limitations

Technical Data

- **Interface**
USB

- **Cable Length**
approx. 1.62 m

- **Keyswitch Lifetime**
Key life: 10 Million operations

Technical Data

- **Layout**
87 US key layout

- **Weight**
Without Packaging 600 +/- 20 g
1.3 lbs
With Packaging 730 g (Approx)
1.6 lbs

- **Dimensions**
Keyboard: 370 x 139 x 19 mm
14.5" x 5.5" x .75"
Packaging: 396 x 210 x 43 mm
15.6" x 8.3" x 1.7"

- **Current Consumption**
40mA (MAX)

- **Humidity**
0~95% RH

- **Operating Temperature**
0°C to +60°C



Technical Data

- **Storage / Transport Temperature**
-20°C to +60°C
- **Packaging Unit**
20 keyboards per master carton
12 master cartons per pallet (252 pcs.)
- **Warranty**
2 years

System Requirements

- USB Port & supporting operating system

Delivery Volume

- Keyboard, Manual

Compatible Operating Systems

- Win 98SE, ME, 2000, XP, XP x 64, Vista

Agency Approvals / Instructions

- CE, FCC Class B, BSMI, RoHS

Order Description

<i>Order Number</i>	<i>Interface</i>	<i>Color</i>
J84-4300LUAUS-2	USB	Black

Other country versions available upon request. (Special conditions apply)

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6500
Internet: www.cherrycorp.com

Support: 800.510.1689
E-Mail: keyboardsupport@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 ZF Electronics Corporation, Last update: Feb 7, 2010_V03

