

Chicago, IL 60609 USA Telephone: +(773) 869 1234 E-mail: saleshelp@tripplite.com



Model #: B060-032

KVM Switch - 32-Port (4-User) 1U Rackmount Cat5 Matrix KVM Switch



Highlights

- Four consoles independently and simultaneously control up to 32 directly connected computers, or over 2,000 when additional KVM's are connected
- Multi-Platform support: PC, Sun, or Mac
- Rackmountable in a 1U design, with 32 available ports...Rackmount Hardware Included
- Inexpensive Cat5 cabling makes cable management a breeze; 500ft distance from Console to switch, or 500ft from Switch to Servers
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's 32-port NetDirector® 1U Rackmount Matrix KVM Switch is the optimal solution for controlling multiple computers (combination of PS/2, USB, or Sun) by four independent, simultaneous users. A single unit occupies a mere 1U of rack space, yet can control up to 32 computers. A maximum of 2,048 computers can be connected through a combination of daisy-chaining and cascading. RJ45 connections allow signals to travel up to 150 meters away(500ft), using ordinary Cat5 cable, while maintaining video resolution. Use either PS/2 or USB console equipment to connect to PS/2, USB, or SUN Servers.

For Government purchasers, B060-032 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

- Console: The Tripp Lite B062-002-PS2 or B062-002-USB Console Interface Module must be used to connect a console (Keyboard, Monitor and Mouse) to the KVM switch
- Computers: The Tripp Lite B054-001-SUN, B054-001-PS2 or B054-001-USB Server Interface Module must be used to connect a computer/server to the KVM switch

Package Includes

- 1 B060-032 KVM Switch
- 1 Power Cord
- 1 Daisy Chain Cable
- 1 CD with Owner's Manual
- 1 set Rackmount Hardware

Features

- Three Level password security: Super Administrator, Administrator, and Users
- Superior video quality up to 1024 x 768 @ 60Hz at 500ft.
- Auto Signal Compensation (ASC) assures optimum video resolution for distances up to 500ft between the switch and the consoles or computers - no dip switch setting required
- PS/2 keyboard and mouse emulation computers boot even when the console focus is elsewhere. Keep Alive feature ensures that the keyboard and mouse work properly even if the switch temporarily loses power

- Daisy chain up to 7 additional B060-032 KVM Switches
- Cascade up to 32 B060-032 KVM switches from each station on the chain
- Up to 2,048 computers on a daisy chained/cascaded installation
- No software required; convenient computer selection via intuitive hotkey combinations or On Screen Display (OSD) menus
- OSD port list automatically expands when stations are added port names are automatically reconfigured when the station sequence is changed
- OSD screen automatically adjusts to resolution changes
- Hot pluggable; add or remove components without having to power off the switch
- USB & PS/2 Consoles can control any combination of USB, PS/2, or SUN computers
- LCD, VGA, SVGA, XGA, and MultiSync support; DDC2B
- Rackmount Hardware Included
- Lifetime firmware upgrading via flash ROM
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW				
# Of Users	4			
Console	No			
Port Control	Hotkeys, OSD			
Max CPU	2048			
PC/Server	VGA, USB or PS/2			
Cat5 KVM Switch	Yes			
IP Remote Access	YES WITH B051-000			
PHYSICAL				
Color	Black			
Style	1U Rackmount			
LCD Monitor (in.)	Not Applicable			
CONNECTIONS				
Ports	32			
FEATURES/SPECIFICATION	DNS			
BTUs	38.9 to 41.7			

Related Items

Required Products

Product Type	Related Model	Description	Qty.
KVM Switches & Accessories	B054-001-SUN	KVM Switch Accessories - SUN Server Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B054-001-PS2	KVM Switch Accessories - PS/2 Server Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B062-002-PS2	KVM Switch Accessories - PS/2 Console Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B054-001-USB	KVM Switch Accessories - USB Server Interface Module for NetDirector Matrix KVM Switches	1

Optional Products

Product Type	Related Model	Description	Qty.
Rackmount Consoles	N001-050-GY	50-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-200-GY	200-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Cables and Accessories	P770-013	13-ft. KVM Switch Daisychain Cable for B060 KVMs	-
Cables and Accessories	P770-10M	33-ft. (10M) KVM Switch Daisychain Cable for B060 KVMs	-
KVM Switches & Accessories	B051-000	KVM Switch Accessories - IP Remote Access Unit	-
Rackmount Consoles	N001-014-GY	14-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
KVM Switches & Accessories	B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	-
Rackmount Consoles	N001-100-GY	100-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-025-GY	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-007-GY	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-005-GY	5-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-075-GY	75-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-010-GY	10-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-250-GY	250-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Extended Warranties	WEXT3-KVM-RMNC	3-Year Extended Warranty - For B060-032 KVM Switch	-
Extended Warranties	WEXT5-KVM-RMNC	5-Year Extended Warranty - For B060-032 KVM switch	-
Rackmount Consoles	N001-125-GY	125-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-003-GY	3-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2910.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.