



- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- △ FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN-LEAD OVER 0.00127 [0.00050] NICKEL ENTIRE POST.
- △ FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN OVER 0.00127 [0.00050] NICKEL ENTIRE POST.

REV	DATE	BY	CHK	DESCRIPTION	DATE	BY	CHK
AD	00						
A2				REVISED PER ECD-11-004820		11MM11	RK HMR

REV	DATE	BY	CHK	DESCRIPTION	DATE	BY	CHK
39							
38							
37							
36							
35							
34							
33							
32							
31							
30							
29							
28							
27							
26							
25							
24							
23							
22							
21							
20							
19							
18							
17							
16							
15							
14							
13							
12							
11							
10							
9							
8							
7							
6							
5							
4							
3							
2							
1							

PLATING: G F E NO. OF POSITIONS PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. THE CUSTOMER'S DRAWING IS THE MASTER. ANY CHANGES MUST BE APPROVED BY THE CUSTOMER AND THE COMPANY.

TE Connectivity
 HEADER ASSEMBLY, MOD II, STACKING, DOUBLE ROW, 0.0254 SQ. POST, UNBROUDED

DATE: 11/11/11
 DRAWING NO: 146487
 CUSTOMER DRAWING

THIS DRAWING IS UNPUBLISHED
 ALL RIGHTS RESERVED

REV	DATE	BY	APP	DESCRIPTION
AD	00			SEE SHEET 1

NO	REF	TYPE	VAL	NO	REF	NO	REF
△	101.19		99.06	39	80		9-146487-0
△	[3.984]		[3.900]				
△	98.65		96.52	38	78		8-146487-9
△	[3.884]		[3.800]				
△	96.11		93.98	37	76		8-146487-8
△	[3.784]		[3.700]				
△	93.57		91.44	36	74		8-146487-7
△	[3.684]		[3.600]				
△	91.03		88.90	35	72		8-146487-6
△	[3.584]		[3.500]				
△	88.49		86.36	34	70		8-146487-5
△	[3.484]		[3.400]				
△	85.95		83.82	33	68		8-146487-4
△	[3.384]		[3.300]				
△	83.41		81.28	32	66		8-146487-3
△	[3.284]		[3.200]				
△	80.87		78.74	31	64		8-146487-2
△	[3.184]		[3.100]				
△	78.33		76.20	30	62		8-146487-1
△	[3.084]		[3.000]				
△	75.79		73.66	29	60		8-146487-0
△	[2.984]		[2.900]				
△	73.25		71.12	28	58		7-146487-9
△	[2.884]		[2.800]				
△	70.71		68.58	27	56		7-146487-8
△	[2.784]		[2.700]				
△	68.17		66.04	26	54		7-146487-7
△	[2.684]		[2.600]				
△	65.63		63.50	25	52		7-146487-6
△	[2.584]		[2.500]				
△	63.09		60.96	24	50		7-146487-5
△	[2.484]		[2.400]				
△	60.55		58.42	23	48		7-146487-4
△	[2.384]		[2.300]				
△	58.01		55.88	22	46		7-146487-3
△	[2.284]		[2.200]				
△	55.47		53.34	21	44		7-146487-2
△	[2.184]		[2.100]				
△	52.93		50.80	20	42		7-146487-1
△	[2.084]		[2.000]				
△	50.39		48.26	19	40		7-146487-0
△	[1.984]		[1.900]				
△	47.85		45.72	18	38		6-146487-9
△	[1.884]		[1.800]				
△	45.31		43.18	17	36		6-146487-8
△	[1.784]		[1.700]				
△	42.77		40.64	16	34		6-146487-7
△	[1.684]		[1.600]				
△	40.23		38.10	15	32		6-146487-6
△	[1.584]		[1.500]				
△	37.69		35.56	14	30		6-146487-5
△	[1.484]		[1.400]				
△	35.15		33.02	13	28		6-146487-4
△	[1.384]		[1.300]				
△	32.61		30.48	12	26		6-146487-3
△	[1.284]		[1.200]				
△	30.07		27.94	11	24		6-146487-2
△	[1.184]		[1.100]				
△	27.53		25.40	10	22		6-146487-1
△	[1.084]		[1.000]				
△	24.99		22.86	9	20		6-146487-0
△	[.984]		[.900]				
△	22.45		20.32	8	18		5-146487-9
△	[.884]		[.800]				
△	19.91		17.78	7	16		5-146487-8
△	[.784]		[.700]				
△	17.37		15.24	6	14		5-146487-7
△	[.684]		[.600]				
△	14.83		12.70	5	12		5-146487-6
△	[.584]		[.500]				
△	12.29		10.16	4	10		5-146487-5
△	[.484]		[.400]				
△	9.75		7.62	3	8		5-146487-4
△	[.384]		[.300]				
△	7.21		5.08	2	6		5-146487-3
△	[.284]		[.200]				
△	4.67		2.54	1	4		5-146487-2
△	[.184]		[.100]				
△	2.13		-	-	2		5-146487-1
△	[.084]		-	-	-		

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	DATE	BY	APP
UNLESS OTHERWISE SPECIFIED:		UNIT	INCHES		
FINISH	PLATING	TEMP	AS SHOWN		
REF	DATE	BY	APP	DESCRIPTION	REVISION
SEE TABLE					

TE Connectivity
 TE CONNECTIVITY
 HEADERS ASSEMBLY, MOD II,
 STACKING, DOUBLE ROW,
 .025 SQ. POST, UNSHROUDED

SIZE: A1 DATE: 11/11/11 DRAWING NO: 146487
 CUSTOMER DRAWING