


- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- △ FINISH: 0.000381 [0.00015] GOLD ON CONTACT AREA, ALL OVER 0.00127 [0.00050] NICKEL ENTIRE POST.



RECOMMENDED HOLE LAYOUT

101.18	99.05	39	40	4-146467-0
[3.984]	[3.900]			
98.65	96.50	38	39	3-146467-9
[3.894]	[3.800]			
96.11	93.98	37	38	3-146467-8
[3.794]	[3.700]			
93.57	91.45	36	37	3-146467-7
[3.694]	[3.500]			
91.03	88.90	35	36	3-146467-6
[3.594]	[3.500]			
88.49	86.36	34	35	3-146467-5
[3.494]	[3.400]			
85.95	83.82	33	34	3-146467-4
[3.394]	[3.300]			
83.41	81.28	32	33	3-146467-3
[3.294]	[3.200]			
80.87	78.74	31	32	3-146467-2
[3.194]	[3.100]			
78.33	76.20	30	31	3-146467-1
[3.094]	[3.000]			
75.79	73.66	29	30	3-146467-0
[2.994]	[2.900]			
73.25	71.12	28	29	2-146467-9
[2.894]	[2.800]			
70.71	68.58	27	28	2-146467-8
[2.794]	[2.700]			
68.17	66.04	26	27	2-146467-7
[2.694]	[2.600]			
65.63	63.50	25	26	2-146467-6
[2.594]	[2.500]			
63.09	60.96	24	25	2-146467-5
[2.494]	[2.400]			
60.55	58.42	23	24	2-146467-4
[2.394]	[2.300]			
58.01	55.88	22	23	2-146467-3
[2.294]	[2.200]			
55.47	53.34	21	22	2-146467-2
[2.194]	[2.100]			
52.93	50.80	20	21	2-146467-1
[2.094]	[2.000]			
50.39	48.26	19	20	2-146467-0
[1.994]	[1.900]			
47.85	45.72	18	19	1-146467-9
[1.894]	[1.800]			
45.31	43.18	17	18	1-146467-8
[1.794]	[1.700]			
42.77	40.64	16	17	1-146467-7
[1.694]	[1.600]			
40.23	38.10	15	16	1-146467-6
[1.594]	[1.500]			
37.69	35.56	14	15	1-146467-5
[1.494]	[1.400]			
35.15	33.02	13	14	1-146467-4
[1.394]	[1.300]			
32.61	30.48	12	13	1-146467-3
[1.294]	[1.200]			
30.07	27.94	11	12	1-146467-2
[1.194]	[1.100]			
27.53	25.40	10	11	1-146467-1
[1.094]	[1.000]			
24.99	22.86	9	10	1-146467-0
[0.994]	[0.900]			
22.45	20.32	8	9	146467-9
[0.894]	[0.800]			
19.91	17.78	7	8	146467-8
[0.794]	[0.700]			
17.37	15.24	6	7	146467-7
[0.694]	[0.600]			
14.83	12.70	5	6	146467-6
[0.594]	[0.500]			
12.29	10.16	4	5	146467-5
[0.494]	[0.400]			
9.75	7.62	3	4	146467-4
[0.394]	[0.300]			
7.21	5.08	2	3	146467-3
[0.294]	[0.200]			
4.67	2.54	1	2	146467-2
[0.194]	[0.100]			
2.13	-	-	1	146467-1
[0.094]	-			
G	F	E	NO. OF POSITIONS	PART NUMBER

AMP Incorporated
 Harrisburg, PA 17105-3606

AMP
 HEADERS, MOD 11,
 STACKING, SINGLE ROW,
 .025 SQ. POST, UNSHROUDED

AMP 100779 146467

CUSTOMER DRAWING