



NO.	DESCRIPTION	REV	NO. OF POSITIONS	PART NUMBER
10119	99.08	39	80	9-146483-0
3.984	3.900		78	8-146483-9
98.65	96.52		37	8-146483-8
3.984	3.700		36	8-146483-7
96.1	93.98		35	8-146483-6
31.03	28.90		34	8-146483-5
3.984	3.500		33	8-146483-4
85.95	83.82		32	8-146483-3
3.984	3.400		31	8-146483-2
83.4	81.28		30	8-146483-1
3.984	3.200		29	8-146483-0
80.87	78.74		28	7-146483-9
73.25	71.12		27	7-146483-8
2.984	2.900		26	7-146483-7
70.77	68.65		25	7-146483-6
2.884	2.800		24	7-146483-5
2.784	2.700		23	7-146483-4
65.17	63.04		22	7-146483-3
2.684	2.600		21	7-146483-2
55.63	53.50		20	7-146483-1
2.584	2.500		19	7-146483-0
2.484	2.400		18	7-146483-9
50.33	48.20		17	7-146483-8
2.384	2.300		16	7-146483-7
47.85	45.72		15	7-146483-6
2.284	2.200		14	7-146483-5
45.37	43.24		13	7-146483-4
2.184	2.100		12	7-146483-3
2.084	2.000		11	7-146483-2
42.89	40.76		10	7-146483-1
40.41	38.28		9	7-146483-0
1.984	1.900		8	6-146483-9
1.884	1.800		7	6-146483-8
37.69	35.56		6	6-146483-7
1.784	1.700		5	6-146483-6
35.21	33.08		4	6-146483-5
1.684	1.600		3	6-146483-4
32.73	30.60		2	6-146483-3
1.584	1.500		1	6-146483-2
30.25	27.94		2	5-146483-1
27.77	25.46		1	5-146483-0
1.484	1.400		1	5-146483-9
25.29	23.16		1	5-146483-8
1.384	1.300		1	5-146483-7
22.81	20.68		1	5-146483-6
1.284	1.200		1	5-146483-5
20.33	18.20		1	5-146483-4
1.184	1.100		1	5-146483-3
17.85	15.72		1	5-146483-2
1.084	1.000		1	5-146483-1
15.37	13.24		1	5-146483-0
0.984	0.900		1	4-146483-9
12.89	10.76		1	4-146483-8
0.884	0.800		1	4-146483-7
10.41	8.28		1	4-146483-6
0.784	0.700		1	4-146483-5
7.93	5.80		1	4-146483-4
0.684	0.600		1	4-146483-3
5.45	3.32		1	4-146483-2
0.584	0.500		1	4-146483-1
2.97	0.84		1	4-146483-0

NO.	DESCRIPTION	REV	NO. OF POSITIONS	PART NUMBER
10119	99.08	39	80	4-146483-0
3.984	3.900		78	3-146483-9
98.65	96.52		37	3-146483-8
3.984	3.700		36	3-146483-7
96.1	93.98		35	3-146483-6
31.03	28.90		34	3-146483-5
3.984	3.500		33	3-146483-4
85.95	83.82		32	3-146483-3
3.984	3.400		31	3-146483-2
83.4	81.28		30	3-146483-1
3.984	3.200		29	3-146483-0
80.87	78.74		28	2-146483-9
73.25	71.12		27	2-146483-8
2.984	2.900		26	2-146483-7
70.77	68.65		25	2-146483-6
2.884	2.800		24	2-146483-5
2.784	2.700		23	2-146483-4
65.17	63.04		22	2-146483-3
2.684	2.600		21	2-146483-2
55.63	53.50		20	2-146483-1
2.584	2.500		19	2-146483-0
2.484	2.400		18	2-146483-9
60.33	58.20		17	2-146483-8
2.384	2.300		16	2-146483-7
47.85	45.72		15	2-146483-6
2.284	2.200		14	2-146483-5
45.37	43.24		13	2-146483-4
2.184	2.100		12	2-146483-3
2.084	2.000		11	2-146483-2
42.89	40.76		10	2-146483-1
40.41	38.28		9	2-146483-0
1.984	1.900		8	1-146483-9
1.884	1.800		7	1-146483-8
37.69	35.56		6	1-146483-7
1.784	1.700		5	1-146483-6
35.21	33.08		4	1-146483-5
1.684	1.600		3	1-146483-4
32.73	30.60		2	1-146483-3
1.584	1.500		1	1-146483-2
30.25	27.94		1	1-146483-1
27.77	25.46		1	1-146483-0
1.484	1.400		1	0-146483-9
25.29	23.16		1	0-146483-8
1.384	1.300		1	0-146483-7
22.81	20.68		1	0-146483-6
1.284	1.200		1	0-146483-5
20.33	18.20		1	0-146483-4
1.184	1.100		1	0-146483-3
17.85	15.72		1	0-146483-2
1.084	1.000		1	0-146483-1
15.37	13.24		1	0-146483-0
0.984	0.900		1	0-146483-9
12.89	10.76		1	0-146483-8
0.884	0.800		1	0-146483-7
10.41	8.28		1	0-146483-6
0.784	0.700		1	0-146483-5
7.93	5.80		1	0-146483-4
0.684	0.600		1	0-146483-3
5.45	3.32		1	0-146483-2
0.584	0.500		1	0-146483-1
2.97	0.84		1	0-146483-0

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN-LEAD OVER 0.00127 [0.000050] NICKEL ENTIRE POST.
- FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN OVER 0.00127 [0.000050] NICKEL ENTIRE POST.

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 11/05/11 BY: [REDACTED] CHECKED: [REDACTED] APPROVED: [REDACTED]

TE Connectivity
HEADER ASSEMBLY, MOD II, STACKING, DOUBLE ROW, .002 SQ. POST, UNDERCUTTED

SIZE: A1 DATE: 11/05/11 DRAWING NO: 100779 G=146483

CUSTOMER DRAWING