



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
 FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN-LEAD OVER 0.00127 [0.000050] NICKEL ENTIRE POST.
 FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN OVER 0.00127 [0.000050] NICKEL ENTIRE POST.

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER	
△	101.13	99.08		39	80	9-146484-0
△	3.984	3.900		38	78	8-146484-9
△	98.65	96.52		38	78	8-146484-9
△	3.984	3.800		37	76	8-146484-8
△	95.1	92.98		37	76	8-146484-8
△	3.978	3.700		36	74	8-146484-7
△	93.57	91.44		36	74	8-146484-7
△	3.984	3.800		35	72	8-146484-6
△	91.03	88.90		35	72	8-146484-6
△	3.984	3.500		34	70	8-146484-5
△	88.44	86.32		34	70	8-146484-5
△	3.484	3.400		33	68	8-146484-4
△	85.95	83.82		33	68	8-146484-4
△	3.984	3.300		32	66	8-146484-3
△	83.41	81.28		32	66	8-146484-3
△	3.984	3.200		31	64	8-146484-2
△	80.87	78.74		31	64	8-146484-2
△	3.984	3.100		30	62	8-146484-1
△	78.33	76.20		30	62	8-146484-1
△	3.084	3.000		29	60	8-146484-0
△	75.79	73.66		29	60	8-146484-0
△	2.984	2.900		28	58	7-146484-9
△	73.25	71.12		28	58	7-146484-9
△	2.884	2.800		27	56	7-146484-8
△	70.71	68.58		27	56	7-146484-8
△	2.784	2.700		26	54	7-146484-7
△	68.17	66.04		26	54	7-146484-7
△	2.684	2.600		25	52	7-146484-6
△	65.63	63.50		25	52	7-146484-6
△	2.584	2.500		24	50	7-146484-5
△	63.09	60.96		24	50	7-146484-5
△	2.484	2.400		23	48	7-146484-4
△	60.55	58.42		23	48	7-146484-4
△	2.384	2.300		22	46	7-146484-3
△	58.01	55.88		22	46	7-146484-3
△	2.284	2.200		21	44	7-146484-2
△	55.47	53.34		21	44	7-146484-2
△	2.184	2.100		20	42	7-146484-1
△	52.93	50.80		20	42	7-146484-1
△	2.084	2.000		19	40	7-146484-0
△	50.39	48.26		19	40	7-146484-0
△	1.984	1.900		18	38	6-146484-9
△	47.85	45.72		18	38	6-146484-9
△	1.884	1.800		17	36	6-146484-8
△	45.31	43.18		17	36	6-146484-8
△	1.784	1.700		16	34	6-146484-7
△	42.77	40.64		16	34	6-146484-7
△	1.684	1.600		15	32	6-146484-6
△	40.23	38.10		15	32	6-146484-6
△	1.584	1.500		14	30	6-146484-5
△	37.69	35.56		14	30	6-146484-5
△	1.484	1.400		13	28	6-146484-4
△	35.15	33.02		13	28	6-146484-4
△	1.384	1.300		12	26	6-146484-3
△	32.61	30.48		12	26	6-146484-3
△	1.284	1.200		11	24	6-146484-2
△	30.07	27.94		11	24	6-146484-2
△	1.184	1.100		10	22	6-146484-1
△	27.53	25.40		10	22	6-146484-1
△	1.084	1.000		9	20	6-146484-0
△	24.99	22.86		9	20	6-146484-0
△	0.984	0.900		8	18	5-146484-9
△	22.45	20.32		8	18	5-146484-9
△	0.884	0.800		7	16	5-146484-8
△	19.91	17.78		7	16	5-146484-8
△	0.784	0.700		6	14	5-146484-7
△	17.37	15.24		6	14	5-146484-7
△	0.684	0.600		5	12	5-146484-6
△	14.83	12.70		5	12	5-146484-6
△	0.584	0.500		4	10	5-146484-5
△	12.29	10.16		4	10	5-146484-5
△	0.484	0.400		3	8	5-146484-4
△	9.75	7.62		3	8	5-146484-4
△	0.384	0.300		2	6	5-146484-3
△	7.21	5.08		2	6	5-146484-3
△	0.284	0.200		1	4	5-146484-2
△	4.67	2.54		1	4	5-146484-2
△	0.184	0.100		-	2	5-146484-1
△	2.13	0.00		-	2	5-146484-1

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER	
△	101.13	99.08		39	80	4-146484-0
△	3.984	3.900		38	78	3-146484-9
△	98.65	96.52		38	78	3-146484-9
△	3.984	3.800		37	76	3-146484-8
△	95.1	92.98		37	76	3-146484-8
△	3.978	3.700		36	74	3-146484-7
△	93.57	91.44		36	74	3-146484-7
△	3.984	3.800		35	72	3-146484-6
△	91.03	88.90		35	72	3-146484-6
△	3.984	3.500		34	70	3-146484-5
△	88.44	86.32		34	70	3-146484-5
△	3.484	3.400		33	68	3-146484-4
△	85.95	83.82		33	68	3-146484-4
△	3.984	3.300		32	66	3-146484-3
△	83.41	81.28		32	66	3-146484-3
△	3.984	3.200		31	64	3-146484-2
△	80.87	78.74		31	64	3-146484-2
△	3.984	3.100		30	62	3-146484-1
△	78.33	76.20		30	62	3-146484-1
△	3.084	3.000		29	60	3-146484-0
△	75.79	73.66		29	60	3-146484-0
△	2.984	2.900		28	58	2-146484-9
△	73.25	71.12		28	58	2-146484-9
△	2.884	2.800		27	56	2-146484-8
△	70.71	68.58		27	56	2-146484-8
△	2.784	2.700		26	54	2-146484-7
△	68.17	66.04		26	54	2-146484-7
△	2.684	2.600		25	52	2-146484-6
△	65.63	63.50		25	52	2-146484-6
△	2.584	2.500		24	50	2-146484-5
△	63.09	60.96		24	50	2-146484-5
△	2.484	2.400		23	48	2-146484-4
△	60.55	58.42		23	48	2-146484-4
△	2.384	2.300		22	46	2-146484-3
△	58.01	55.88		22	46	2-146484-3
△	2.284	2.200		21	44	2-146484-2
△	55.47	53.34		21	44	2-146484-2
△	2.184	2.100		20	42	2-146484-1
△	52.93	50.80		20	42	2-146484-1
△	2.084	2.000		19	40	2-146484-0
△	50.39	48.26		19	40	2-146484-0
△	1.984	1.900		18	38	1-146484-9
△	47.85	45.72		18	38	1-146484-9
△	1.884	1.800		17	36	1-146484-8
△	45.31	43.18		17	36	1-146484-8
△	1.784	1.700		16	34	1-146484-7
△	42.77	40.64		16	34	1-146484-7
△	1.684	1.600		15	32	1-146484-6
△	40.23	38.10		15	32	1-146484-6
△	1.584	1.500		14	30	1-146484-5
△	37.69	35.56		14	30	1-146484-5
△	1.484	1.400		13	28	1-146484-4
△	35.15	33.02		13	28	1-146484-4
△	1.384	1.300		12	26	1-146484-3
△	32.61	30.48		12	26	1-146484-3
△	1.284	1.200		11	24	1-146484-2
△	30.07	27.94		11	24	1-146484-2
△	1.184	1.100		10	22	1-146484-1
△	27.53	25.40		10	22	1-146484-1
△	1.084	1.000		9	20	1-146484-0
△	24.99	22.86		9	20	1-146484-0
△	0.984	0.900		8	18	146484-9
△	22.45	20.32		8	18	146484-9
△	0.884	0.800		7	16	146484-8
△	19.91	17.78		7	16	146484-8
△	0.784	0.700		6	14	146484-7
△	17.37	15.24		6	14	146484-7
△	0.684	0.600		5	12	146484-6
△	14.83	12.70		5	12	146484-6
△	0.584	0.500		4	10	146484-5
△	12.29	10.16		4	10	146484-5
△	0.484	0.400		3	8	146484-4
△	9.75	7.62		3	8	146484-4
△	0.384	0.300		2	6	146484-3
△	7.21	5.08		2	6	146484-3
△	0.284	0.200		1	4	146484-2
△	4.67	2.54		1	4	146484-2
△	0.184	0.100		-	2	146484-1
△	2.13	0.00		-	2	146484-1

THIS DRAWING IS A CONTROLLED DOCUMENT. IZM/TE CONNECTIVITY

DIMENSIONS: IN (INCHES)
 UNLESS OTHERWISE SPECIFIED
 DIMENSIONS: IN (INCHES)
 UNLESS OTHERWISE SPECIFIED

DATE: 11/07/09
 DRAWING NO: 100779G-146484
 CUSTOMER DRAWING

REVISIONS: 11MM11 RJK HMR
 REVISED PER EDD-11-04820