



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
 FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN-LEAD OVER 0.00127 [0.00050] NICKEL ENTIRE POST.
 FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN OVER 0.00127 [0.00050] NICKEL ENTIRE POST.

NO.	REF.	DESCRIPTION	DATE	BY	APP.
101	19	99.06	39	40	9-146465-0
13.984	13.900	38	39	8-146465-9	
98.50	96.52	37	38	8-146465-8	
95.11	93.98	36	37	8-146465-7	
93.57	91.44	35	36	8-146465-6	
88.44	86.36	34	35	8-146465-5	
3.684	3.600	33	34	8-146465-4	
3.484	3.400	32	33	8-146465-3	
85.93	83.82	31	32	8-146465-2	
81.71	79.74	30	31	8-146465-1	
78.33	76.20	29	30	8-146465-0	
74.23	71.12	28	29	7-146465-9	
70.77	68.58	27	28	7-146465-8	
68.17	66.04	26	27	7-146465-7	
2.684	2.600	25	26	7-146465-6	
65.60	63.50	24	25	7-146465-5	
63.02	60.96	23	24	7-146465-4	
2.484	2.400	22	23	7-146465-3	
59.47	57.34	21	22	7-146465-2	
2.284	2.200	20	21	7-146465-1	
55.81	53.89	19	20	7-146465-0	
50.30	48.26	18	19	6-146465-9	
1.984	1.900	17	18	6-146465-8	
47.80	45.72	16	17	6-146465-7	
45.31	43.18	15	16	6-146465-6	
42.77	40.64	14	15	6-146465-5	
1.684	1.600	13	14	6-146465-4	
40.23	38.10	12	13	6-146465-3	
1.584	1.500	11	12	6-146465-2	
37.69	35.58	10	11	6-146465-1	
30.07	27.94	9	10	6-146465-0	
1.284	1.200	8	9	5-146465-9	
24.93	22.86	7	8	5-146465-8	
1.884	1.800	6	7	5-146465-7	
19.91	17.78	5	6	5-146465-6	
1.784	1.700	4	5	5-146465-5	
1.684	1.600	3	4	5-146465-4	
1.584	1.500	2	3	5-146465-3	
1.484	1.400	1	2	5-146465-2	
1.384	1.300	-	1	5-146465-1	
1.284	1.200	-	-	-	
1.184	1.100	-	-	-	
1.084	1.000	-	-	-	

NO.	REF.	DESCRIPTION	DATE	BY	APP.
101	19	99.06	39	40	4-146465-0
13.984	13.900	38	39	3-146465-9	
98.50	96.52	37	38	3-146465-8	
95.11	93.98	36	37	3-146465-7	
93.57	91.44	35	36	3-146465-6	
88.44	86.36	34	35	3-146465-5	
3.684	3.600	33	34	3-146465-4	
3.484	3.400	32	33	3-146465-3	
85.93	83.82	31	32	3-146465-2	
81.71	79.74	30	31	3-146465-1	
78.33	76.20	29	30	3-146465-0	
74.23	71.12	28	29	2-146465-9	
70.77	68.58	27	28	2-146465-8	
68.17	66.04	26	27	2-146465-7	
2.684	2.600	25	26	2-146465-6	
65.60	63.50	24	25	2-146465-5	
63.02	60.96	23	24	2-146465-4	
2.484	2.400	22	23	2-146465-3	
59.47	57.34	21	22	2-146465-2	
2.284	2.200	20	21	2-146465-1	
55.81	53.89	19	20	2-146465-0	
50.30	48.26	18	19	1-146465-9	
1.984	1.900	17	18	1-146465-8	
47.80	45.72	16	17	1-146465-7	
45.31	43.18	15	16	1-146465-6	
42.77	40.64	14	15	1-146465-5	
1.684	1.600	13	14	1-146465-4	
40.23	38.10	12	13	1-146465-3	
1.584	1.500	11	12	1-146465-2	
37.69	35.58	10	11	1-146465-1	
30.07	27.94	9	10	1-146465-0	
1.284	1.200	8	9	146465-9	
24.93	22.86	7	8	146465-8	
1.884	1.800	6	7	146465-7	
19.91	17.78	5	6	146465-6	
1.784	1.700	4	5	146465-5	
1.684	1.600	3	4	146465-4	
1.584	1.500	2	3	146465-3	
1.484	1.400	1	2	146465-2	
1.384	1.300	-	1	146465-1	
1.284	1.200	-	-	-	
1.184	1.100	-	-	-	
1.084	1.000	-	-	-	

THIS DRAWING IS A CONTROLLED DOCUMENT. IT IS THE PROPERTY OF TE Connectivity. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.

TE Connectivity
 HEADER ASSEMBLY, MOD II,
 STACKING, SINGLE ROW,
 0.025 SQ. POST, UNSHROUDED

DATE: 00779 G=146465
 CUSTOMER DRAWING