



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- ▲ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
 ▲ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
 ▲ FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN-LEAD OVER 0.00127 [0.00050] NICKEL ENTIRE POST.
 ▲ FINISH: 0.00254-0.00508 [0.00100-0.00200] MATTE TIN OVER 0.00127 [0.00050] NICKEL ENTIRE POST.

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
▲	101.19	99.06	39	80	9-146489-0
▲	98.65	96.52	38	78	8-146489-9
▲	96.11	93.98	37	76	8-146489-8
▲	93.57	91.44	36	74	8-146489-7
▲	91.03	88.90	35	72	8-146489-6
▲	88.49	86.36	34	70	8-146489-5
▲	85.95	83.82	33	68	8-146489-4
▲	83.41	81.28	32	66	8-146489-3
▲	80.87	78.74	31	64	8-146489-2
▲	78.33	76.20	30	62	8-146489-1
▲	75.79	73.66	29	60	8-146489-0
▲	73.25	71.12	28	58	7-146489-9
▲	70.71	68.58	27	56	7-146489-8
▲	68.17	66.04	26	54	7-146489-7
▲	65.63	63.50	25	52	7-146489-6
▲	63.09	60.96	24	50	7-146489-5
▲	60.55	58.42	23	48	7-146489-4
▲	58.01	55.88	22	46	7-146489-3
▲	55.47	53.34	21	44	7-146489-2
▲	52.93	50.80	20	42	7-146489-1
▲	50.39	48.26	19	40	7-146489-0
▲	47.85	45.72	18	38	6-146489-9
▲	45.31	43.18	17	36	6-146489-8
▲	42.77	40.64	16	34	6-146489-7
▲	40.23	38.10	15	32	6-146489-6
▲	37.69	35.56	14	30	6-146489-5
▲	35.15	33.02	13	28	6-146489-4
▲	32.61	30.48	12	26	6-146489-3
▲	30.07	27.94	11	24	6-146489-2
▲	27.53	25.40	10	22	6-146489-1
▲	24.99	22.86	9	20	6-146489-0
▲	22.45	20.32	8	18	5-146489-9
▲	19.91	17.78	7	16	5-146489-8
▲	17.37	15.24	6	14	5-146489-7
▲	14.83	12.70	5	12	5-146489-6
▲	12.29	10.16	4	10	5-146489-5
▲	9.75	7.62	3	8	5-146489-4
▲	7.21	5.08	2	6	5-146489-3
▲	4.67	2.54	1	4	5-146489-2
▲	2.13	-	-	2	5-146489-1

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
▲	101.19	99.06	39	80	4-146489-0
▲	98.65	96.52	38	78	3-146489-9
▲	96.11	93.98	37	76	3-146489-8
▲	93.57	91.44	36	74	3-146489-7
▲	91.03	88.90	35	72	3-146489-6
▲	88.49	86.36	34	70	3-146489-5
▲	85.95	83.82	33	68	3-146489-4
▲	83.41	81.28	32	66	3-146489-3
▲	80.87	78.74	31	64	3-146489-2
▲	78.33	76.20	30	62	3-146489-1
▲	75.79	73.66	29	60	3-146489-0
▲	73.25	71.12	28	58	2-146489-9
▲	70.71	68.58	27	56	2-146489-8
▲	68.17	66.04	26	54	2-146489-7
▲	65.63	63.50	25	52	2-146489-6
▲	63.09	60.96	24	50	2-146489-5
▲	60.55	58.42	23	48	2-146489-4
▲	58.01	55.88	22	46	2-146489-3
▲	55.47	53.34	21	44	2-146489-2
▲	52.93	50.80	20	42	2-146489-1
▲	50.39	48.26	19	40	2-146489-0
▲	47.85	45.72	18	38	1-146489-9
▲	45.31	43.18	17	36	1-146489-8
▲	42.77	40.64	16	34	1-146489-7
▲	40.23	38.10	15	32	1-146489-6
▲	37.69	35.56	14	30	1-146489-5
▲	35.15	33.02	13	28	1-146489-4
▲	32.61	30.48	12	26	1-146489-3
▲	30.07	27.94	11	24	1-146489-2
▲	27.53	25.40	10	22	1-146489-1
▲	24.99	22.86	9	20	1-146489-0
▲	22.45	20.32	8	18	146489-9
▲	19.91	17.78	7	16	146489-8
▲	17.37	15.24	6	14	146489-7
▲	14.83	12.70	5	12	146489-6
▲	12.29	10.16	4	10	146489-5
▲	9.75	7.62	3	8	146489-4
▲	7.21	5.08	2	6	146489-3
▲	4.67	2.54	1	4	146489-2
▲	2.13	-	-	2	146489-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISED:	DATE:	BY:	CHK:	APP:

DRAWING NO: 100779
 REV: G
 DATE: 11/06/99
 CUSTOMER DRAWING: 11/06/99

THIS DRAWING IS A CONTROLLED DOCUMENT.
 REVISED: DATE: BY: CHK: APP:

DRAWING NO: 100779
 REV: G
 DATE: 11/06/99
 CUSTOMER DRAWING: 11/06/99

DRAWING NO: 100779
 REV: G
 DATE: 11/06/99
 CUSTOMER DRAWING: 11/06/99