



- ▲ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- ▲ POST: COPPER ALLOY.
- ▲ POST FINISH: 0.00076 [0.00030] GOLD IN AREA G, 0.00254-0.00508 [0.00100-0.00200] BRIGHT TIN-LEAD IN AREA H, ALL OVER 0.00127 [0.00050] NICKEL.
- ▲ POINT OF MEASUREMENT FOR PLATING THICKNESS.
- ▲ RECESSED DATE CODE.
- 6. CSA LOGO HOT STAMPED WHITE ON HOUSING.
- ▲ BOARD RETENTION WHERE INDICATED.
- ▲ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION
- ▲ POST FINISH: 0.00076 [0.00030] GOLD IN AREA G, 0.00254-0.00508 [0.00100-0.00200] MATTE TIN IN AREA H, ALL OVER 0.00127 [0.00050] NICKEL.
- ▲ ROHS 2002/95/EC COMPLIANT
- ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

1, 4	1, 4	19.81 [7.80]	17.02 [6.70]	17.78 [7.00]	3	8	▲	▲	7-534978-1
1,3	1,3	17.27 [6.80]	14.48 [5.70]	16.24 [6.00]	2	6	▲	▲	7-534978-0
2,22,43,64	2,22,43,64	174.75 [6.880]	171.96 [6.720]	172.72 [6.800]	64	130	▲	▲	6-534978-9
2,17,33,39	2,17,33,39	136.65 [5.380]	133.86 [5.270]	134.62 [5.300]	49	100	▲	▲	6-534978-8
2, 24, 47	2, 24, 47	15.18 [5.900]	15.070 [5.100]	15.100 [5.100]	47	96	▲	▲	6-534978-7
2, 3, 4	2, 3, 4	24.89 [9.800]	22.10 [8.700]	22.86 [9.000]	5	12	▲	▲	6-534978-6
2, 18, 34	2, 18, 34	98.55 [3.880]	95.76 [3.720]	96.52 [3.800]	34	70	▲	▲	6-534978-5
2, 23, 47, 69	2, 23, 47, 69	182.05 [7.380]	159.26 [6.270]	160.02 [7.300]	69	140	▲	▲	6-534978-4
2, 20, 40, 59	2, 20, 40, 59	182.05 [6.380]	159.26 [6.270]	160.02 [6.300]	59	120	▲	▲	6-534978-3
2, 18, 37, 54	2, 18, 37, 54	149.35 [5.880]	146.56 [5.720]	147.32 [5.800]	54	110	▲	▲	6-534978-2
2, 20, 39	2, 20, 39	111.25 [4.380]	108.46 [4.270]	109.22 [4.300]	39	80	▲	▲	6-534978-1
2, 18, 35	2, 18, 35	101.09 [3.980]	98.30 [3.870]	99.06 [3.900]	35	72	▲	▲	6-534978-0
2, 15, 29	2, 15, 29	85.85 [3.380]	83.06 [3.270]	83.82 [3.300]	29	60	▲	▲	5-534978-9
8, 13, 18	8, 13, 18	73.15 [2.880]	70.36 [2.720]	71.12 [2.800]	24	50	▲	▲	5-534978-8
5, 10, 15	5, 10, 15	60.45 [2.380]	57.66 [2.270]	58.42 [2.300]	19	40	▲	▲	5-534978-7
4, 9, 14	4, 9, 14	53.37 [2.180]	52.58 [2.100]	53.34 [2.100]	17	36	▲	▲	5-534978-6
3, 8, 13	3, 8, 13	47.75 [1.880]	44.96 [1.720]	45.72 [1.800]	14	30	▲	▲	5-534978-5
5, 6, 7	5, 6, 7	40.13 [1.580]	37.34 [1.420]	38.10 [1.500]	11	24	▲	▲	5-534978-4
4, 5, 6	4, 5, 6	35.05 [1.380]	32.26 [1.270]	33.02 [1.300]	9	20	▲	▲	5-534978-3
3, 4, 5	3, 4, 5	29.97 [1.180]	27.18 [1.070]	27.94 [1.100]	7	16	▲	▲	5-534978-2
2, 33, 67, 99	2, 33, 67, 99	283.85 [10.380]	260.86 [10.270]	261.62 [10.300]	99	200	▲	▲	5-534978-1
1, 4	1, 4	19.81 [7.80]	17.02 [6.70]	17.78 [7.00]	3	8	▲	▲	2-534978-1
1,3	1,3	17.27 [6.80]	14.48 [5.70]	16.24 [6.00]	2	6	▲	▲	2-534978-0
2,22,43,64	2,22,43,64	174.75 [6.880]	171.96 [6.720]	172.72 [6.800]	64	130	▲	▲	1-534978-9
2,17,33,39	2,17,33,39	136.65 [5.380]	133.86 [5.270]	134.62 [5.300]	49	100	▲	▲	1-534978-8
2, 24, 47	2, 24, 47	15.18 [5.900]	15.070 [5.100]	15.100 [5.100]	47	96	▲	▲	1-534978-7
2, 3, 4	2, 3, 4	24.89 [9.800]	22.10 [8.700]	22.86 [9.000]	5	12	▲	▲	1-534978-6
2, 18, 34	2, 18, 34	98.55 [3.880]	95.76 [3.720]	96.52 [3.800]	34	70	▲	▲	1-534978-5
2, 23, 47, 69	2, 23, 47, 69	182.05 [7.380]	159.26 [6.270]	160.02 [7.300]	69	140	▲	▲	1-534978-4
2, 20, 40, 59	2, 20, 40, 59	182.05 [6.380]	159.26 [6.270]	160.02 [6.300]	59	120	▲	▲	1-534978-3
2, 18, 37, 54	2, 18, 37, 54	149.35 [5.880]	146.56 [5.720]	147.32 [5.800]	54	110	▲	▲	1-534978-2
2, 20, 39	2, 20, 39	111.25 [4.380]	108.46 [4.270]	109.22 [4.300]	39	80	▲	▲	1-534978-1
2, 18, 35	2, 18, 35	101.09 [3.980]	98.30 [3.870]	99.06 [3.900]	35	72	▲	▲	1-534978-0
2, 15, 29	2, 15, 29	85.85 [3.380]	83.06 [3.270]	83.82 [3.300]	29	60	▲	▲	534978-9
8, 13, 18	8, 13, 18	73.15 [2.880]	70.36 [2.720]	71.12 [2.800]	24	50	▲	▲	534978-8
5, 10, 15	5, 10, 15	60.45 [2.380]	57.66 [2.270]	58.42 [2.300]	19	40	▲	▲	534978-7
4, 9, 14	4, 9, 14	53.37 [2.180]	52.58 [2.100]	53.34 [2.100]	17	36	▲	▲	534978-6
3, 8, 13	3, 8, 13	47.75 [1.880]	44.96 [1.720]	45.72 [1.800]	14	30	▲	▲	534978-5
5, 6, 7	5, 6, 7	40.13 [1.580]	37.34 [1.420]	38.10 [1.500]	11	24	▲	▲	534978-4
4, 5, 6	4, 5, 6	35.05 [1.380]	32.26 [1.270]	33.02 [1.300]	9	20	▲	▲	534978-3
3, 4, 5	3, 4, 5	29.97 [1.180]	27.18 [1.070]	27.94 [1.100]	7	16	▲	▲	534978-2
2, 33, 67, 99	2, 33, 67, 99	283.85 [10.380]	260.86 [10.270]	261.62 [10.300]	99	200	▲	▲	534978-1

OBSOLETE

FINISH	ROW M	ROW N	K	J	B	A	NO OF POSN	PART NUMBER
	BOARD RETENTION	LOCATION						

THIS DRAWING IS A CONTROLLED DOCUMENT. IN CHARGE/DATE
 DATE
 REVISIONS
 DESCRIPTION
 DATE
 11MM111 RKC HMR

TE Connectivity

HEADER ASSY, MOD II, DOUBLE ROW,
 0.64 [0.025] SQUARE POST/BOARD RETENTION FEATURE

00779 ©=534978