

(2,54mm) .100"
BBS, BBL, BHS, BBD, BDL SERIES

MACHINED BOARD STACKING STRIPS

Mates with:
 SS, SD, HSS, SL, SDL,
 ESS, ESD

FEATURES

- Low profile design achieves (3,89mm) .153" board spacings when mated with SL series.
- Choice of precision machined (BXX Series) or coined (LBS Series) terminals.
- Approach the reliability of a permanent connection with the flexibility of a separable connection.

SPECIFICATIONS

For complete specifications see www.samtec.com?BBS, www.samtec.com?BBD, www.samtec.com?BBL or www.samtec.com?BDL



BBS, BBD, BBL, BDL
 Insulator Material:
 Black Glass Filled Polyester (BBS, BBD, BBL)
 Black High Temp Nylon (BDL)
Temperature Range:
 -55°C to +125°C
Terminal Material:
 Phosphor Bronze or Brass
Plating:
 Au or Sn over 50µ" (1,27µm) Ni
Current Rating:
 1A
RoHS Compliant:
 Yes
Lead-Free Solderable:
 Wave only

SPECIFICATIONS

For complete specifications see www.samtec.com?BHS

BHS
 Same as BBS except:
 Insulator Material:
 Black Liquid Crystal Polymer
RoHS Compliant:
 Yes
Lead-Free Solderable:
 Wave, or reflow with all Au

Note: Some lengths, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM