



- △ .00030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN-LEAD ON SOLDER TAILS ALL OVER, .000050 NICKEL
- △ WINDOWS SHOWN ON SIDE OF HOUSING ARE MOLDERS OPTION.
- △ REFER TO NO. OF POSN. IN CHART FOR NUMBER OF SURFACES WHICH ARE COPLANAR.
- △ VACUUM COVER DESIGNED FOR .160 [4mm] DIA NOZZLE. VACUUM COVER TO BE REMOVED AFTER SOLDERING.
- 5 PACKAGED IN TAPE & REEL PER EIA-481 SPECIFICATIONS. SEE CHART FOR TAPE WIDTHS.
- △ .265 [6.75mm] MIN TARGET AREA FOR VACUUM PICK-UP.
- △ HOUSING: PPA. CONTACT: PHOSPHOR BRONZE. VACUUM COVER: ALUMINUM.
- △ VACUUM COVER SHOWN IN PHANTOM LINE.
- △ AMP LOGO PRESENCE AND LOCATION OPTIONAL.
- △ .00030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN ON SOLDER TAILS, ALL OVER, .000050 NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

SIZE	F	E	A	NO OF POSN	PART NUMBER	
△ OBSOLETE	44mm	.560	11	.644	24	147378-9
△ OBSOLETE	68mm	2.450	49	2.544	190	147378-8
△ OBSOLETE	88mm	1.950	39	2.044	80	147378-7
△ OBSOLETE	72mm	1.450	29	1.544	60	147378-6
△ OBSOLETE	56mm	1.200	24	1.294	50	147378-5
△ OBSOLETE	56mm	.950	19	1.044	40	147378-4
△ OBSOLETE	44mm	.700	14	.794	30	147378-3
△ OBSOLETE	32mm	.450	9	.544	20	147378-2
△ OBSOLETE	32mm	.200	4	.294	10	147378-1
△ OBSOLETE	44mm	.560	11	.644	24	147378-9
△ OBSOLETE	68mm	2.450	49	2.544	190	147378-8
△ OBSOLETE	88mm	1.950	39	2.044	80	147378-7
△ OBSOLETE	72mm	1.450	29	1.544	60	147378-6
△ OBSOLETE	56mm	1.200	24	1.294	50	147378-5
△ OBSOLETE	56mm	.950	19	1.044	40	147378-4
△ OBSOLETE	44mm	.700	14	.794	30	147378-3
△ OBSOLETE	32mm	.450	9	.544	20	147378-2
△ OBSOLETE	32mm	.200	4	.294	10	147378-1
SUPERSEDED BY 5-147378-1						
	TAPE WIDTH	F	E	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. SEE THE DRAWING FOR THE CONTROLLED DOCUMENT NUMBER.

DESIGNER	DATE	REVISED BY	DATE
108-1093			
114-25035			

RECEPTACLE ASSEMBLY, VERTICAL, DOUBLE ROW, SURFACE MOUNT, AMPHENOL SYSTEM 50

CUSTOMER DRAWING