



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
03 ₂	SEE ECN 80-0084	EB 2/14/80	T.S. 2/19/80
03 ₃	REDRAWN IN CAD PER ECN 88-0678	EFH 1/10/90	KCM

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468, AND FED. SPEC L-P-403	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B196, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.089
CONTACT	.021

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. DEC. ANGLES
± 1/64 ± .005 ± °

These drawings and specifications are the property of Genl Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DESIGNED BY
9/7/69
CHECKED BY
B.D.
9/8/69
DRAWN BY
G.B.
9/8/69



AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

USE ASSY PROCEDURE
408-04833
NO. AP. (20-010)

TITLE
OSM STRAIGHT CABLE JACK
DIRECT SOLDER ATTACHMENT

SIZE B	CODE IDENT NO. 26805	2002-5016-00	REV 03 ₃
SCALE 5:1	SHEET 1 OF 1		

NOTES:

- DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE
- CAPTURED CENTER CONTACT

CUSTOMER DRAWING

AMP PART # 1050859-1
SHEET 1 OF 1 REV A