REV.	DATE	DESCRIPTION
A	12/01/99	UPDATE DRAWING ADD DOUBLE BRAID
B	05/23/03	UPDATE DRAWING FORMAT / MODIFY FERRULE



RECOMMENDED
CABLE STRIPPING DIM'S







NOTES:

1. CRIMPED FERRULE
   HEX SIZE .151"
2. CRIMPED CONTACT PIN
   SQ. CRIMP SIZE 0.7mm

8				
7				
6				
5	CONTACT PIN	BRASS	GOLD	1
4	FERRULE	COPPER	NICKEL	1
3	CONTACT PIN	PHOS. BRONZE	GOLD	1
2	INSULATOR	DELRIN	NATURAL	1
1	BODY	BRASS	NICKEL	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	05/23/03
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/122/122375.DWG

Amphenol Connex

PART DESCRIPTION
TNC CRIMP PLUG – DOUBLE BRAID
(RG-174/U, 188A/U, 316/U CABLE)

PART NO. 122375

DWG. NO.	REV.	SIZE	SCALE
122375.DWG	B	A	NA

Downloaded from Elcodis.com electronic components distributor