NOTES:		31-5640-1010	REVISIONS	REVISIONS		
<ol> <li>MATERIALS AND FINISHES:         BDDY - NICKEL PLATED ZINC DIE CAST         INSULATOR - WHITE NORYL         CENTER CONTACT - GDLD PLATED PHOSPHER BRONZE         MOUNTING PINS - BRIGHT TIN PLATED BRASS         TERMINALS - TIN PLATED COPPER WIRE         ACCOMDIDATES UP TO 125 THICK PC BOARD AND         188 PANEL THICKNESS.         JDIELECTRIC WITHSTANDING VOLLTAGE: 1500VRMS MAX.         4. INSULATION RESISTANCE: 5000MQ MIN.         5. NOMINAL IMPEDANCE: 50 OHMS.         6. MOUNTING HARDWARE, SEPARATLY SUPPLIED, MUST BE TICK WHEN ASSEMBLING TO PANEL.         7. DO NOT SCALE THIS DRAWING.         8. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE AFT</li> </ol>		DRAMING NO. REV THIRD ANGLE PROJ.	DESCRIPTION  OFFICIAL ENG. RELEASE TO MFG.  SEE SHEET 1 FOR REVISIONS  SEE SHEET 1 FOR REVISIONS	4/26/96	ECO APPR 39213 JM/RV 41291 CPM/ 45255 CPM/	
# .079 ±000 2 PL ±003   PC HOLE MOUNTING	95 ±003 2 PL	.82 .380 DIA .34 .4 .1.38	PANEL CUT-E	.218/221 † 505/510		
15 025 (	32 19 09	.500-28UNEF-2A	CUSTOMER DUTLINE	DI /C		
			<u> </u>	D.W.G.	•	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±0.05 (0,127 mm) ± 11 ±0.05 (0,127 mm) ± 10.05 (0,127	REFERENCE E EAR 962338-2	DATE   DATE	BNC JACK RT/ANGLE PCB MOUNT ZINC DIE CAST  CODE 10 DWG SIZE DRAWING H2.DVG 74868 B		ration perations	

31-5640-1010 DRAWING NO. THIRD ANGLE PROJ.

REVISIONS