THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- -
© COPYRIGHT - - By - - ALL RIGHTS RESERVED.

LAST	DATE
AJ	16

REVISIONS

P	LTR	DESCRIPTION	DATE	DRN	APVD
	S1	REVISED PER ECO-11-005030	11MAR11	RK	HMR

1. SEE I.S. SHEET 2028-1





VIEW X



VIEW Y

RECOMMENDED STRIP LENGTH

		TBD	47.22 [1.859]	Y	BXS 7004-501	7-225092-6 AMP	225612-2	51695-2	225081-7	7-225092-6
	OBSOLETE	220015-1	37.08 [1.460]	X	TIME AA-5888	7-2250902-5 AMP	225560-3	2-51695-2	225901-3	7-225092-5
	OBSOLETE	220015-1	46.02 [1.812]	X	TIME AA-5886	7-225092-4 AMP	1-331987-0	1-51695-2	225081-1	7-225092-4
	OBSOLETE	220015-1	46.81 [1.843]	X	TIME AA-5887	7-225092-3 AMP	225612-2	4-51695-0	225081-6	7-225092-3
SUPERSEDED BY	225092-2	–	–	–	–	–	–	–	–	7-225092-2
SUPERSEDED BY	225092-1	–	–	–	–	–	–	–	–	7-225092-1
	OBSOLETE	–	–	–	–	–	–	–	–	1-225092-7
	OBSOLETE	–	–	–	–	–	–	–	–	1-225092-6
	OBSOLETE	–	–	–	–	–	–	–	–	1-225092-5
	OBSOLETE	220015-1	47.22 [1.859]	Y	RG-214/U	10688470 AMP	331987	51695-2	225081-1	1-225092-2
		220015-1	47.22 [1.859]	Y	RG-393/U	1-225092-1 AMP	225490-1	2-51695-3	225081-1	1-225092-1
		220015-3	46.43 [1.828]	X	MICRODOT 250-4172, 250-4208	1-225092-0 AMP	225612-2	2-51695-1	225901-1	1-225092-0
		220015-3	46.43 [1.828]	X	MICRODOT 250-4171, 250-4207	225092-9 AMP	225612-1	2-51695-1	225901-2	225092-9
SUPERSEDED BY	414160-3	220015-1	47.22 [1.859]	Y	RG-115A/U	225092-8 AMP	1-331987-3	2-51695-1	225081-2	225092-8
		220015-1	47.22 [1.859]	Y	RG-225/U	00779M39012/01B0007 AMP & DATE CODE (YY-WW)	331987	51695-8	225081-1	225092-7
	OBSOLETE	–	–	–	–	–	–	–	–	225092-6
	OBSOLETE	–	–	–	–	–	–	–	–	225092-5
	OBSOLETE	–	–	–	–	–	–	–	–	225092-4
		220015-1	47.22 [1.859]	X	RG-213/U	00779M39012/01B0007 AMP & DATE CODE (YY-WW)	1-331987-3	51695-2	225081-1	225092-2
		220015-1	47.22 [1.859]	Y	RG-214/U	00779M39012/01B0008 AMP & DATE CODE (YY-WW)	331987	51695-2	225081-1	225092-1
		CRIMP TOOL	A MAX	STRIP LENGTH VIEW	CABLE SIZE	STAMPING	3 FERRULE QTY=1	2 CONTACT QTY=1	1 PLUG ASSY QTY=1	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM[INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± 0.41 [.016]
ANGLES ± –

MATERIAL –
FINISH –

DRN	M SNEED	2-22-91
CHK	R HENRY	2-22-91
APVD	R HENRY	2-22-91

PRODUCT SPEC 108-12019
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME PLUG,WEATHERPROOF,SERIES N
–

SIZE A1 CAGE CODE 00779 DRAWING NO C-225092 RESTRICTED TO –

CUSTOMER DRAWING SCALE 2:1 SHEET 1 OF 1 REV S1

4806 (3/11)

Downloaded from Elcodis.com electronic components distributor