



| REVISIONS | | | |
|-----------|---------------------------|----------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| 02 8 | REVISED PER ECN 97-0358-2 | 10/24/97 | TWag |

| ELECTRICAL | MECHANICAL | ENVIRONMENTAL | HOUSING | MATERIAL | FINISH |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Nominal Impedance (Ohms) 50 Frequency Range (GHz) DC to 18 Volt Rating (VRMS MAX) Sea Level 335 VSWR 1.05 + .005f GHz Insertion Loss (dB MAX) .03 √f GHz RF Leakage (dB MIN) -(60-f[GHz]) Corona, 70,000 Ft (VRMS MIN) 250 Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1000 Contact Resistance (Milliohms MAX) Center Contact 3.0 Outer Contact 2.0 Cable to Housing N/A RF High Potential Sea Level (VRMS MIN) 5 MHz 670 IR.(Megohms MIN) 10,000 | Interface Dimensions MIL-STD-348A, Fig 310-2 Recommended Mating Torque 7-10 In-Lbs Mating Characteristics: Insertion (MAX Lbs) 3.0 Withdrawal (MIN Oz) 1.0 Force to Engage and Disengage (In/Lbs MAX) 2 Center Contact Captivation Axial (Lbs) 6.0 Radial (In/Oz) 4.0 Weight (Grams) 2.9 | Temperature Rating -65°C To +125°C Vibration MIL-STD-202, Method 204 204, Condition B Shock MIL-STD-202, Method 213, Condition I Thermal Shock MIL-STD-202, Method 107, Condition B Moisture Resistance MIL-STD-202, Method 106, Except Vibration Shall Be Omitted Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray | HOUSING DIELECTRIC CENTER CONTACT | STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 TFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H | PASSIVATE PER QQ-P-35 N/A GOLD PLATE PER MIL-G-45204 |
| | | | COMPONENT | MATERIAL | FINISH |
| | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± ° | DRAWN BY EJC DATE 4/17/68 CHECKED BY BWC 4/17/68 APP'D BY D. NANIA 4/17/68 USE ASSY PROCEDURE NO. AP. N/A | AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 |
| | | | TITLE OSM FLANGE MOUNT JACK RECEPTACLE - STRAIGHT TERMINAL | | |
| | | | SIZE B | CODE IDENT NO. 26805 | 2052-1201-02 |
| | | | SCALE 5 : 1 | | REV 02 8 |
| | | | SHEET 1 OF 1 | | |

CUSTOMER DRAWING

AMP PART # 1052523-1
SHEET 1 OF 1 REV A