


RECOMMENDED PANEL CUTOUT



PCB CONFIGURATION

- △ ZINC PER QQ-Z-363.
- △ POLYMETHYLPENTENE, GENERAL PURPOSE.
- △ BERYLLIUM COPPER PER QQ-C-530.
- △ BRASS PER ASTM-B-453.
- △ BRASS PER ASTM-B-16.
- △ NICKEL PLATE PER QQ-N-290, 3.81 μm [.000150] MINIMUM THICK.
- △ TIN PLATE PER ASTM-B-545, 3.81 μm [.000150] MINIMUM THICK.
- △ GOLD PLATE PER ASTM-B-488, 0.76 μm [.000030] MINIMUM THICK.
- 9. SEE INSTRUCTION SHEET 408-2769.

5413506-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
DRAWING		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
DIMENSIONS		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
TOLERANCES UNLESS OTHERWISE SPECIFIED		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
FRACTIONS		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
DECIMALS		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
ANGLES		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
HIDDEN SURFACES		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
FIRST ANGLE PROJECTION		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
SEE NOTES 1-5		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
SEE NOTES 6-8		REV. 16	DATE	DESCRIPTION	BY	CHK	APP
CUSTOMER DRAWING		REV. 16	DATE	DESCRIPTION	BY	CHK	APP

5413506-1
PART NUMBER

TYS Electronics Corporation
 Harrisburg, PA 17105-3608

JACK, RIGHT ANGLE, PCB, 75 OHM, TNC SERIES

REV. 16
 DATE 05/14/05
 DESCRIPTION 00779(G)=5413506

CUSTOMER DRAWING