



DESIGNED FOR USE WITH RG-142/U OR EQUIVALENT	REV	DESCRIPTION	DATE	APPROVED
CABLE ENTRY DIAMETER MINIMUM	--	UPDATED		<i>[Signature]</i>
FERRULE		.216		
SLEEVE		.119		
DIELECTRIC		.042		
CONTACT		.039		

HOUSING CLAMP NUT SLEEVE	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
DIELECTRIC	NYLON OF ZYTEL #101 PER MIL-M-20693A, TYPE 1	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
O - RING	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating -65°C to +165°C
Frequency Range (GHz) DC to 12	Recommended Mating Torque 7-10 In-Lbs	Vibration MIL-STD-202, Method 204, Condition D.
Volt Rating (VRMS MAX) Sea Level 335	Mating Characteristics: Insertion (MAX Lbs) 3.0	Shock MIL-STD-202, Method 213, Condition I.
VSWR 1.15 +.01 fGHz	Withdrawal (MIN Oz) 1.0	Thermal Shock MIL-STD-202, Method 107, Condition B.
Insertion Loss (dB MAX) .06 √fGHz	Force to Engage and Disengage (In-Lbs MAX) 2.0	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) -(60-fGHz)	Center Contact Captivation Axial (Lbs) 6.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 250	Radial (In-Oz) N/A	
Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1000	Cable Retention Axial Force (Lbs MIN) 4.0	
Contact Resistance (Milliohms MAX) Center Contact 2.0	Torque (In-Oz) N/A	
Outer Contact 2.0	Weight (Grams) TBD	
Cable to Housing .05		
RF High Potential Sea Level (VRMS MIN @ 5 MHz) 670		
IR (Megohms MIN) 10,000		

COMPONENT	MATERIAL	FINISH
<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °</small>		
<small>These drawings and specifications are the property of Osmil Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.</small>		
DRAWN BY: RMK DATE: 4/14/69 CHECKED BY: PW 4/15/69 APP'D BY: D.NANIA 4/18/77		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
USE ASSY PROCEDURE 408-04810 NO. AP. (20-055)		TITLE OSM STRAIGHT CABLE JACK CRIMP ATTACHMENT
SIZE B	CODE IDENT NO. 26805	REV 04 ₂
SCALE 3 : 1	2032-5007-00	SHEET 1 OF 1

CUSTOMER DRAWING AMP PART # 1051861-1 SHEET 1 OF 1 REV A