

DESIGNED FOR USE WITH .141 DIA S.R. CABLE	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.143
CONTACT	.038

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
01_1	RELEASED	3/11/99	Tlbag

ELECTRICAL	
Nominal Impedance (Ohms)	50
Frequency Range (GHz) DC to	18
Volt Rating (VRMS MAX)	
@ Sea Level	500
VSWR 1.05+.01 f(GHz)	
Insertion Loss (dB MAX)	.03x $\sqrt{f(GHz)}$
RF Leakage (dB MIN)	-[90-f(GHz)]
Corona, 70,000 Ft (VRMS MIN)	375
Dielectric Withstanding Voltage	
(VRMS MIN) @ Sea Level	1500
Contact Resistance (Milliohms MAX)	
Center Contact	3.0
Outer Contact	2.0
Cable to Housing	0.5
RF High Potential @ Sea Level	
(VRMS MIN @ 5 MHz)	1000
I.R.(Megohms MIN)	5000

MECHANICAL	
Interface Dimensions MIL-STD-348A, Fig 310.2	
Mating Characteristics:	
Insertion (MAX Lbs)	3
Withdrawal (MIN Oz)	1
Force to Engage & Disengage (In-Lbs MAX)	2
Center Contact Captivation	
Axial (Lbs)	6.0
Cable Retention	
Axial Force (Lbs MIN)	60
Torque (In-Oz MIN)	55
Weight (Grams)	TBD

ENVIRONMENTAL
Temperature Rating -65°C to +105°C
Vibration MIL-STD-202, Method 204, Condition D
Shock MIL-STD-202, Method 213, Condition I
Thermal Shock MIL-STD-202, Method 107, Condition B
Moisture Resistance MIL-STD-202, Method 106
Corrosion - MIL-STD-202, Method 101, Condition B

.XXX = in
XX.X = mm (REF)

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. ± 1/64 DEC. ±.005 ANGLES ± 1°

DRAWN BY TIM WAGNER DATE 12/16/98
CHECKED BY
APP'D BY TIM WAGNER 3/11/99

These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASS'Y PROCEDURE
NO. A.P. 408-04857 (20-709)

AMP

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

TITLE OSM STRAIGHT CABLE JACK - DIRECT SOLDER ATTACHMENT CAPTURED CENTER CONTACT

SIZE	CODE IDENT NO.		REV
B	26805	2002-5155-00	01_1

SCALE 5:1 SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1329599-1
SHEET 1 OF 1 REV A

Downloaded from Elcodis.com electronic components distributor