


DESIGNED FOR USE WITH	RG 180/U, 195 CABLE
CABLE ENTRY DIAMETER	MINIMUM
CLAMP NUT	.160
COLLAR	.105
CONTACT	.043

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01	2	REVISD	JAC 6/13/99
A	REVISD PER 0020-0176-01	G.V. 8/14/02	6/16/99

COMPONENT	MATERIAL	FINISH
HOUSING COUPLING NUT CLAMP NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
CENTER CONTACT COLLAR	BRASS PER ASTM-B-16.	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLDY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY RR	DATE 10/11/79	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
FRAC. DEC. ANGLES	CHECKED BY RRS	10/12/79	
± 1/64 ±.005 ± 1°	APP'D BY JK	10/12/79	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF AMP INTERCONNECT DIV. AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF PRODUCTS WITHOUT WRITTEN PERMISSION.			TITLE "DSM" RIGHT ANGLE CABLE PLUG CLAMP ATTACHMENT
USE ASS'Y PROCEDURE NO. AP. 20-077			SIZE B CODE IDENT. NO. 26805 SCALE 4:1
			SHEET 1 OF 1 REV 01 2

NOTES:
1. CAPTURED CENTER CONTACT

.XXX = In
XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1051143-1
SHEET 1 OF 1 REV A