



DESIGNED FOR USE WITH RG-214/U, RG-225/U & RG-393/U	
CABLE ENTRY DIAMETER MINIMUM	.095
CONTACT	.291
COLLAR	.447
WASHER	.457
WEDGE	.437
CLAMP NUT	

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	17SEP79	PR
02 ₀	SEE ECN 81-0929-1	3-30-81	RD
03 ₀	92-0010 AND 92-0110-2 (2 OF 2)	04-25-92	RB 5/13/92

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. N/A	Temperature Rating -65°C to +165°C
Frequency Range (GHz) DC to 15	Recommended Mating Torque 12 -15 in-lbs	Vibration MIL-STD-202, Method 204, Condition B
Volt Rating (VRMS MAX) Sea Level 500	Mating Characteristics: Insertion (MAX Lbs) 2.0	Shock MIL-STD-202, Method 213, Condition 1
VSWR 1.10 +.01 (fGHz)	Withdrawal (MIN Oz) 2.0	Thermal Shock MIL-STD-202, Method 107, Condition B
Insertion Loss (dB MAX) .07 √(fGHz)	Force to Engage and Disengage (in-Lbs MAX) 2.0	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) -[90-(fGHz)]	Center Contact Captivation Axial (Lbs) 6.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 375	Radial (in-Oz) N/A	
Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1500	Cable Retention Axial Force (Lbs) 40.0	
Contact Resistance (Milliohms MAX) Center Contact 3.0	Torque (in-Oz) N/A	
Outer Contact 2.0	Weight (Grams) TBD	
Cable to Housing .5		
RF High Potential Sea Level (VRMS MIN) 5 MHz 1,000		
IR (Megohms MIN) 10,000		

COMPONENT	MATERIAL	FINISH
HOUSING CLAMP NUT	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290 OVER COPPER STRIKE
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COLLAR WASHER WEDGE	BRASS PER QQ-B-626 COMP. 360, HALF HARD	GOLD PLATE PER MIL-G45204 OVER COPPER PLATE PER MIL-C-14550

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY RR	DATE 9-11-79	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	CHECKED BY R.D. SMITH	9-13-79	
	APPROVED BY GH	9-21-79	

TITLE OST STRAIGHT CABLE JACK CLAMP ATTACHMENT			
SIZE B	CODE IDENT NO. 26805	3102-7214-10	REV 03 ₀
SCALE 2 : 1			SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1080552-1
SHEET 1 OF 1 REV A