REV.	DATE	DESCRIPTION
NC	04/14/03	INITIAL RELEASE



RECOMMENDED CABLE
STRIPPING DIM'S





NOTE:

1. CRIMPED FERRULE
   HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN
   HEX CRIMP SIZE 118"

	DESCRIPTION	MATERIAL	FINISH	QTY
8				
7				
6				
5				
4	FERRULE	COPPER	NICKEL	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	PHENOLIC	YELLOW	1
1	BODY	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	04/14/03
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/182/182130.DWG

Amphenol Connex

PART DESCRIPTION
UHF CRIMP PLUG
(FOR BELDEN 8214, 9913, 9914, LMR400 CABLE)

PART NO. 182130

DWG. NO.	REV.	SIZE	SCALE
182130.DWG	NC	A	NA

Downloaded from Elcodis.com electronic components distributor