



FEATURES:

- Mounts in panels up to 6.35 (.25)
- Hermetic Seal – 50 PSI differential pressure
- Leakage rate less than 10^{-7} cc/sec of tracer gas at one atmosphere

MATERIALS:

Body and Fittings – Brass, Alloy 360, 1/2 Hard

Dielectric – PTFE

Center and Intermediate Contacts – Gold Plated Beryllium Copper, Cond. HT.or Brass per body.

Gasket – Silicone rubber per ZZ-R-765, Class 11, Grade 50.

Finish:

Body and Fittings – Tarnish resistant.

Center and Intermediate Contacts – Gold plate per requirements of MIL-C-49142.

Marking: POMONA 4388

RATINGS:

Nominal Impedance: 50 Ohms

ORDERING INFORMATION: Model 4388

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

6/9/99

SY/EH/LS

S:\Engineering\Release\DataSheets\FIukeDataSheetd4388_1_01.doc

Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90261 (800) 444-6785 or (425) 446-6010

More drawings available at www.pomonaelectronics.com

Page 1 of 1