



## 75Ω BNC BULKHEAD ADAPTERS

| Description  |           | Dimensions, inches (millimeters) |            |            |           | Notes |      | Mtg. Hole | UG No. | 75Ω Type | Amphenol Number               | Fig. |
|--------------|-----------|----------------------------------|------------|------------|-----------|-------|------|-----------|--------|----------|-------------------------------|------|
|              |           | a                                | b          | d          | e         | Plt.  | Ins. |           |        |          |                               |      |
| Gasketed     | Jack-Jack | 1.40(35.6)                       | .750(19.0) | .666(16.9) | .172(4.4) | P15   | D1   | Y         | —      | T1       | <a href="#">31-70020</a>      | 1    |
| Not Gasketed | Jack-Jack | 1.28(32.5)                       | .750(19.0) | .492(12.5) | .216(5.5) | P7    | D23  | Y         | —      | T2       | <a href="#">31-220N-75RFX</a> | 1 ▲  |
| Not Gasketed | Jack-Jack | 1.40(35.6)                       | .800(20.3) | .664(16.8) | .181(4.6) | P17   | D1   | Y         | —      | T2       | <a href="#">31-220N-75</a>    | 1    |
| Isolated     | Jack-Jack | 1.28(32.5)                       | .625(15.9) | .460(11.7) | .190(4.8) | P17   | D12  | Y         | —      | T2       | <a href="#">31-4803-75</a>    | 2 ▲  |

▲ distributor stocked