


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	16NOV01	[Signature]
B	PER EC 0U20-0116-01-03	16NOV01	[Signature]

COMPONENT	MATERIAL	FINISH
COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	ELECTRO-POLISHED
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	DATE	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	SWA	9/11/84	
FRAC. + 1/64	DEC. + .005	ANGLES + °	TITLE 7mm PRECISION TO 'OSN' JACK ADAPTER
These drawings and specifications are the property of M/A CDM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items) without written permission.	USE ASSY PROCEDURE		NO. AP. N/A
	SIZE	CODE IDENT NO.	REV
	B	26805	7482-2300-00
SCALE	3:1		SHEET 1 OF 1

- NOTES:
1. CAPTURED CENTER CONTACT
 2. FREQ: DC ~ 18.0 GHz
 3. VSWR (MAX): 1.015 +.0025f(GHz)

.XXX = in
XX.X = mm (REF)

CUSTOMER DRAWING
AMP PART # 1062022-1
SHEET 1 OF 1 REV B