


- NOTES:
1. CAPTURED CENTER CONTACT
  2. FREQ. RANGE: DC-18.0 GHz
  3. VSWR: 1.03 +.004 f(GHz) (MAX)

XXX = in  
XX.X = mm (REF)

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>1</sub>	REVISED	5/14/98	<i>[Signature]</i> 3/31/99
B	PER EC 0U20-0116-01-03	13NOV01	<i>[Signature]</i> 13NOV01

COMPONENT	MATERIAL	FINISH
CONT. FINGERS (x2)	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	N/A
HOUSING COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	ELECTRO-POLISHED
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY CD	DATE 6/30/82	 <b>AMP Incorporated</b> 140 Fourth Avenue Waltham, MA 02451-7599
FRAC. DEC. ANGLES + 1/64 +.020 * °	CHECKED BY PCJ	7/1/82	
	APP'D BY MK	7/2/82	
These drawings and specifications are the property of AMP Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			TITLE <b>7mm PRECISION TO "OSP" JACK ADAPTER</b>
USE ASSY PROCEDURE		NO. A.P. N/A	SIZE <b>B</b>
			CODE IDENT NO. <b>26805</b>
			SCALE <b>4:1</b>
			REV <b>01<sub>1</sub></b>
			SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1059720-1  
SHEET 1 OF 1 REV B