


Model 73046
N Type Jack to TNC Plug Adapter



Model 73046
N Type Jack to TNC Plug Adapter

Materials

Center Conductor: Phosphor Bronze, Gold Plated
Connector Body: Brass, Nickel Plated
Insulators: PTFE

Specifications

Impedance: 50 Ω
Frequency Range: DC - 11GHz
Contact Resistance:
 Center Conductor: ≤ 2.0 m Ω
 Outer Conductor: ≤ 0.2 m Ω
Insulation Resistance: ≥ 5000 M Ω
Dielectric Withstand Voltage: 1500V
 For CE compliance, do not hold in hand when
 voltages exceed 33 Vrms / 70 Vdc.
Number of Insertions: 500 cycles minimum

Ordering Information

Model: **73046**

Features

- DC - 11GHz bandwidth.
- Connectors are precision machined.

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 **International:** 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.