


- △ BRASS PER 00-B-626.
- △ BERYLLIUM COPPER PER ASTM-B-196
- △ NYLON PER ASTM-D-4066, BLACK
- △ POLYMETHYLPENTENE GENERAL PURPOSE, NATURAL
- △ .000030 MINIMUM GOLD PER MIL-G-45204.
- △ .000050 MINIMUM GOLD PER MIL-G-45204.
- △ .000100 MINIMUM GOLD PER MIL-G-45204.
- △ RG-174/U, RG-179A/U, RG-187/U, AND 21-598.
- △ SHIELDED CABLE #26-NA5-702 CLASS A & C, AND MIL-W-16878 TYPES E & EE, SHIELDED CABLE #24-NA5-702 CLASS A & C, AND MIL-W-16878 TYPES E & EE, SHIELDED CABLE #22-NA5-702 CLASS C, AND MIL-W-16878 TYPE E, AND MIL-C-7078A TYPE I NUMBER 1 DIELECTRIC .068 O.D.
- 10. SEE IS 408-1770
- △ NYLON PER ASTM-D-4066, NATURAL
- △ DIELECTRIC MATERIAL: VALOX 325 WHITE



CONTACT PLATING	SHELL PLATING	WEIGHT	CABLE OR WIRE SIZE	CRIMP TOOL	Y	FERRULE QTY±1	SPRING RETENTION QTY±1	PIN ASSY QTY±1	PART NUMBER
△△	△△	.030 OUNCES	-	-	.032±.003	-	-	-	2-201143-5
△△	△△	.030 OUNCES	-	-	.032±.003	-	-	-	2-201143-4
△△	△△	.030 OUNCES	-	-	.032±.003	-	-	-	201143-7
△△	△△	.030 OUNCES	-	-	.032±.003	-	-	-	201143-5
△△	△△	.030 OUNCES	-	-	.042±.003	-	-	-	201143-3
△△	△△	.030 OUNCES	-	-	.032±.003	-	-	-	201143-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

INCHES: 1/16, 1/8, 3/16, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 1

REVISED TO REFLECT: 10B-12021

AMP  
 TFC Electronics  
 Harrisburg, PA 17105-3608

PIN, MINIATURE SERIES

SEE TABLE A1 00778 201143

CUSTOMER DRAWING