

1. HOUSING: LCP, UL 94V-0 RATED, BLACK.
   CONTACTS: PHOSPHOR BRONZE.
   RETENTION LEG: BRASS.
2. CONTACTS: 0.76µm GOLD FOR A LENGTH OF 1.20 MIN STARTING 0.50 MAX FROM MATING END, 1.27µm-3.81µm TIN-LEAD FOR A LENGTH OF 3.43 MIN FROM OPPOSITE END, BOTH OVER 1.27µm MIN NICKEL.
3. CONNECTOR WILL ACCOMMODATE MATING PRINTED CIRCUIT BOARD OF 1.60±0.07 THICKNESS.
4. POSITION TOLERANCE APPLIES AT CONTACT TIP ONLY.
5. DIMENSION APPLIES TO CONTACTS 1, 36 THRU 40, 41 THRU 43, 45, 46 AND 75 THRU 80.
6. DIMENSION APPLIES TO CONTACTS 2 THRU 35, 44, AND 47 THRU 74.
7. RETENTION LEG: 3.81µm MIN TIN-LEAD OVER 1.27µm MIN NICKEL.
8. RECOMMENDED PC BOARD THICKNESS IS 2.36 TO 3.81.
9. CONTACTS: 0.76µm GOLD FOR A LENGTH OF 1.20 MIN STARTING 0.50 MAX FROM MATING END, 1.27µm-3.81µm MATTE TIN FOR A LENGTH OF 3.43 MIN FROM OPPOSITE END, BOTH OVER 1.27µm MIN NICKEL.
10. RETENTION LEGS: 3.81µm MIN HALT TIN.
11. CONTACTS: 0.38µm GOLD FOR A LENGTH OF 1.20 MIN STARTING 0.50 MAX FROM MATING END, 1.27µm-3.81µm MATTE TIN FOR A LENGTH OF 3.43 MIN FROM OPPOSITE END, BOTH OVER 1.27µm MIN NICKEL.
12. CONTACTS: 0.38µm GOLD FOR A LENGTH OF 1.20 MIN STARTING 0.50 MAX FROM MATING END, 1.27µm-3.81µm TIN-LEAD FOR A LENGTH OF 3.43 MIN FROM OPPOSITE END, BOTH OVER 1.27µm MIN NICKEL.
13. **OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI**

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	H	REVISED PER EC 0513-0254-05	02JUN99	BM	EB
	J	REVISED PER EC 0513-0311-05	02JUN99	BM	EB
	J1	REVISED PER ECO-10-000445	06JAN10	KK	AEG

OBSOLETE	787900-4
	~~787900-3~~
	787900-2
	787900-1
FINISH	PART NUMBER

DRN	D.FOLTZ	13-Sep-96	AMP Incorporated, Harrisburg, PA 17105-3608
CH	J.CRANE	17-Sep-96	
APVD	J.CRANE	17-Sep-96	RECEPTACLE ASSEMBLY, VERTICAL, 80 POSITION, PRESS FIT, CHAMP™ BLINDMATE .050 SERIES I
PRODUCT SPEC	108-1568		
APPLICATION SPEC	-		
WEIGHT	-		
CUSTOMER DRAWING		SIZE A	DRAWING NO 00779-787900
		SCALE 2:1	SHEET 1 OF 1
		RESTRICTED TO -	REV J1

Downloaded from Elcodis.com electronic components distributor