



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. MATERIAL: HOUSING & COVER - THERMOPLASTIC, BLACK. TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE. .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
3. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
5. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
6. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
7. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS. TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
8. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

REVISED		REVISIONS	
DATE	DESCRIPTION	DATE	BY
11/26/83	BMI W/M		

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE: 11/26/83	
DRAWING NO: 553596		REV: 00	
DRAWING TITLE: PLUG ASSEMBLY, 14 POSITION		DRAWING NO: 1174838	
DRAWING NO: 553596		DRAWING NO: 1174838	
DRAWING TITLE: PLUG ASSEMBLY, 14 POSITION		DRAWING NO: 1174838	
DRAWING NO: 553596		DRAWING NO: 1174838	
DRAWING TITLE: PLUG ASSEMBLY, 14 POSITION		DRAWING NO: 1174838	
DRAWING NO: 553596		DRAWING NO: 1174838	